

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.O.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
L-6383

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator
Amoco Production Company ✓
Address of Operator
P. O. Box 68 Hobbs, NM 88240

Location of Well
UNIT LETTER E 1980 FEET FROM THE North LINE AND 860 FEET FROM
THE West LINE, SECTION 2 TOWNSHIP 23-S RANGE 28-E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name
State GO Gas Com
9. Well No.
1
10. Field and Pool, or Wildcat
Wildcat Atoka
12. County
Eddy

15. Elevation (Show whether DF, RT, CR, etc.)
2008.5' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☒
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to abandon Atoka and test Bone Springs:

Open well and bleed off pressure. Ran cast iron bridge plug and set at 11,100' and cap with 35' of cement. Perforate 8740'-90' with 1 DDJPF. Run tailpipe to approx. 8800' and spot 200 gallons of 15% HCL acid. Pull tailpipe to 8680'. Acidize with 5000 gallons of 15% HCL acid and flush with brine water. When productivity of zone is determined, zone will be either permanently abandoned by cast iron bridge plug or temporarily abandoned by retrievable bridge plug. If cast iron bridge plug is to be used, it will be set at 8600'. Perforate 7654'-80' w/2 DPJSPF. If retrievable bridge plug is to be used, it will be set at 7750'. Bottom of tailpipe at 7580'. Acidize 7654'-80' w/10,000 gallons of gelled 15% HCL acid. Swab well and shut-in for evaluation.

0+4-NMOCD, A 1-Hou 1-Pennzoil 1-TX Pac 1-D. Hartman 1-Susp 1-GPM

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Greg Mitchell TITLE Admin. Analyst DATE 6-30-81

APPROVED BY W.D. Gussert TITLE SUPERVISOR, DISTRICT II DATE JUL 21 1981

CONDITIONS OF APPROVAL, IF ANY: