

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

NEW MEXICO CONSERVATION COMMISSION

MAY 21 1979

O. C. C.
ARTESIA, OFFICE

30-015-22928

Form C-101
Revised 1-1-65

5A. Indicate Type of Lease
STATE ☒ FEDERAL ☐

5. State Oil & Gas Lease No.
L-4764

7. Well Agreement Name

8. Name of Lessee
Oscar State

9. Well No.
1

10. Field and Loc. or Section
Wildcat

12. County
Eddy

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work

b. Type of Well DRILL ☒ DEEPEN ☐ PLUG BACK ☐
OIL WELL ☐ GAS WELL ☒ OTHER ☐ SINGLE ZONE ☒ MULTIPLE ZONE ☐

1. Name of Operator

The Superior Oil Company ✓

2. Address of Operator

P. O. Box 71, Conroe, Texas 77301

3. Location of Well

UNIT LETTER G LOCATED 1980 FEET FROM THE North LINE
1980' East LINE OF SEC. 36 TWP. 24S RGE. 29E

21. Elevations (Show whether DE, RT, etc.)

3101.6 ft.

21A. Kind & Status Plug. Bond

Blanket

19. Proposed Depth

14,300'

19A. Formation

Morrow

20. Type of Casing

Rotary

21B. Drilling Contractor

22. Approx. Date Work will start

6-1-79

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
Drive	20"	94#	50'	-	-
17-1/2"	13-3/8"	48#	500'	170 SX	Surface
12-1/4"	10-3/4"	40.5#	3300'	750 SX	Surface
9-5/8"	7-5/8"	26.4# & 29.7#	10,500'	425 SX	8500'
6-1/2"	5-1/2" Liner	20#	14,300'	250 SX	10,200'

BOP - See Attached Sheet

Gas Not Dedicated

APPROVAL VALID
FOR 90 DAYS UNLESS
DRILLING COMMENCED,

EXPIRES 8-23-79

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Leo J. Laux, Jr. Title Engineer Assistant Date 5/18/79

(This space for State Use)

APPROVED BY W.A. Gessert TITLE SUPERVISOR, DISTRICT II DATE MAY 23 1979

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to
surface behind 13 3/8" & 10 3/4" casing