

BK Exploration Corp.
 Williams "35" Com. No. 2
 NE/SW/4 Sec. 35-23S-28E
 Eddy Co., New Mexico

3040' KB, 21' AGL

17.5" hole

12.25" hole

8.5" hole

13.375", 54.5# H-40, STC @ 0-512'
 625 sxs., cmt. circulated

9.625", 36# K-55, STC @ 0-2550'
 1500 sxs., TOC estimated @ surface

Proposed CIBP @ 5850'
 w/ 35' cmt. to 5815'

TOC @ 5594'

FORMATION	TOP, KB
Alluvium	0
Top Salt	480'
Base Salt	2440'
Delaware Sands	2644'
Bone Spring	6334'

5897'
 Delaware perfs, 10 holes

CIBP @ 6080', cmt. to 6045'

6106'
 Delaware perfs, 16 holes

CIBP @ 6200', cmt. to 6183'

6212'
 Delaware perfs, 54 holes

CIBP @ 10,953', cmt. to 10,923'

4.5" PER @ 10,953'

7", 16-23# N-80, S-95, LTC @ 0-11,223'
 1275 sxs., TOC @ 5595' by CBL

6.125" hole

11,812'
 Atoka perfs

11,825'

PBTD 13,050'
 TD 13,100'

4.5" liner, 13.5# N-80, LTC @ 10,953-13,097'