

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Permian Brine Sales & Service</i>		Lease <i>Eugenie</i>		Well #. <i>2</i>	
Location of Well	Unit <i>1285 S 447 W</i>	Section <i>17</i>	Township <i>22</i>	Range <i>22</i>	County <i>Eddy</i>
Drilling Contractor	Type of Equipment <i>Cable tools to start approx. 10-16-79</i>				
* <i>Witness</i> APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
* <i>8"</i>	<i>5 1/2"</i>	<i>17</i>		<i>350</i>	<i>circ.</i>
* <i>4 3/4"</i>	<i>2 7/8"</i>	<i>6.4</i>		<i>580</i>	<i>"</i>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____ (Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <i>8"</i> Size of Casing <i>5 1/2</i> Sacks cement required _____					
Type of Shoe used <i>guide</i> Float collar used _____ Btm 3 jts welded _____					
TD of hole <i>289</i> Set <i>289</i> Feet of <i>5 1/2</i> inch <i>175</i> # Grade <i>J-55</i>					
New-used csg. @ <i>289</i> with <i>125</i> sacks neat cement around shoe					
+ _____ sax _____ additives <i>2% cc</i>					
Plug down @ <i>12:05</i> (AM) (PM) Date <i>11-6-79</i>					
Cement circulated <i>yes</i> No. of Sacks <i>25 sax</i>					
Cemented by _____ Witnessed by <i>Grossett</i>					

Permian Brine Sales
Eugenie #2

M-17-22-27

11-20-79

Ran 2 7/8 to 590 and cemented with 100 SX class C 2% cc
Circulated 20 SX. Centerlizer @ 10 ft - 280 ft - 320 ft
395 ft & 445 ft Basket located @ 570 ft & 580 ft
TD @ 616 Plug down @ 1:30 pm BJ Cemented
2 7/8 Tubing used But Tested to 6000 PSI