

OIL CONSERVATION DIVISION
 RECEIVED
 P. O. BOX 2088
 SANTA FE, NEW MEXICO 87504
 MAR 24 1983

Form C-103
 Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

O. C. D.
 ARTESIA, OFFICE

3a. Indicate Type of Lease
 State Fee

3. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
 USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. Well GAS WELL OTHER

Name of Operator
 DINERO OPERATING COMPANY

7. Unit Agreement Name

8. Farm or Lease Name
 McNutt

Address of Operator
 P. O. DRAWER 105C5, MIDLAND, TEXAS 79702

9. Well No.
 1

Location of well
 DEPTH LETTER L 1980 FEET FROM THE South LINE AND 630 FEET FROM West 1980

10. Field and Pool, or Wildcat
~~Wildcat Bone Spring~~
Wildcat Bone Spring Delaware

LINE, SECTION 12 TOWNSHIP 24-S RANGE 28-E NMPM.

15. Elevation (Show whether DF, RT, CR, etc.)
 2977.6 G.L.

12. County
 Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
 NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

REMEDIAL WORK
 PARTIALLY ABANDON
 ALTER CASING
 PLUG AND ABANDON
 CHANGE PLANS
 OTHER

REMEDIAL WORK
 COMMENCE DRILLING OPNS.
 CASING TEST AND CEMENT JOB
 OTHER Plug back from Bone Spring to Delaware
 ALTERING CASINGS
 PLUG AND ABANDONMENT

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed operations.) SEE RULE 1103.

- 1-13-83 Rig up workover unit and fish tubing and rods.
 Set Dowell Model "3" 10,000 psi Bridge Plug at 26,280'. POH and filled hole with brine water. Rig up Schlumberger and run TOT and CBL Logs.
- 1-17-83 Rig down workover unit.
- 1-26-83 Rig up workover unit. Perofrate 5674-5684' with 2JSPF (21 holes).
 Acidize with 5,000 gallons 15% MSR Acid. average 5 barrels per min. at 2580 psi.
- 2-1-83 Set Dowell Model "3" 10,000 psi bridge plug at 5050'. Perforate 5912-5940' with 2 JSPF (56 holes). Acidize with 6,000 gallons 6.3 barrels per min. at 3,500 psi.
- 2-10-83 Fractured zone with 25,000 gallons gel and 41,000# 20/40 sand.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
Lavanda Naman TITLE Production Supervisor DATE March 18, 1983