

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

CONSERVATION DIVISION

RECEIVED BY P. O. BOX 2088
SANTA FE, NEW MEXICO 87501
APR 1 1985
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
Name of Operator Tenneco Oil Company ✓		5. State Oil & Gas Lease No.
Address of Operator 7990 IH 10 West, San Antonio, TX 78230		7. Unit Agreement Name
Location of Well UNIT LETTER J 1500 FEET FROM THE South LINE AND 1980 FEET FROM East LINE, SECTION 13 TOWNSHIP 24S RANGE 27E NMPM.		8. Farm or Lease Name Harrison CL13
15. Elevation (Show whether DF, RT, GR, etc.) 2973.4		9. Well No. 1
12. County Eddy		10. Field and Pool, or Wildcat Malaga

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPS. <input type="checkbox"/> CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/> OTHER <input type="checkbox"/>
---	--	---	---

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Ran 9 jts. of 20" 94# K-55 Butt casing (378.44) with 20" weatherford weld on Guide Shoe (.8') set casing at 338'. Cemented with 750 SXS trinity lite + 1/4 Focle followed with 200 SXS Class "C" + 2% CaCl₂ Flocc. Plug pumped to 296' with 150 PSI on 1/29/85. WOC 18 hrs. Top cmt. at surface. Resume operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by Don Lindberg TITLE Drilling Engineer DATE 3-10-85
Original Signed By
Leslie A. Clements
Supervisor District 11
APPROVED BY _____ DATE APR 2 1985
CONDITIONS OF APPROVAL, IF ANY: