

RECEIVED

OCT - 7 1992

Form C-103  
Revised 1-1-89Submit 3 Copies  
to Appropriate  
District OfficeDISTRICT I  
P.O. Box 1980, Hobbs, NM 88240DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410State of New Mexico  
Energy, Minerals and Natural Resources DepartmentO. C. D.  
ARTESIA OFFICE

## OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-015-27072
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-3479
7. Lease Name or Unit Agreement Name  Pinnacle State
8. Well No. 3
9. Pool name or Wildcat Herradura Bend, East Delaware

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator Fortson Oil Company ✓	
3. Address of Operator 301 Commerce St., Suite 3301, Fort Worth, TX 76102	
4. Well Location Unit Letter <u>K</u> : <u>1980</u> Feet From The <u>South</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>36</u> Township <u>22 South</u> Range <u>28 East</u> NMPM Eddy County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3102' GL	

## 11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
 PULL OR ALTER CASING ☐  
 OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
 COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
 CASING TEST AND CEMENT JOB ☐  
 OTHER: Cement Squeeze, Perforate & Treat ☒

## 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

September 29, 1992:

Set a Howco EZ drill cement retainer at 6070' K.B.

Mixed 25 sacks Micro-Matrix cement and 25 sacks Neat cement. Sqz perfs 6119 - 6114 - 6095 - 6085

Reversed out estimated 3 barrels of cement.

Spotted 250 gallons 10% Acetic Acid.

Perforated 5990' - 6010' (80 holes).

As of October 1, 1992 preparing to test above perforations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sheryl L. Jonas TITLE Agent for Fortson Oil Co. DATE 10/06/92  
 TYPE OR PRINT NAME Sheryl L. Jonas TELEPHONE NO. (915) 683-551

(This space for State Use)

ORIGINAL SIGNED BY

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE OCT 7 1992

CONDITIONS OF APPROVAL IF ANY: