

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☐ Other ☐		1b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. REMOVR. ☐ Other ☐		5. LEASE DESIGNATION AND SERIAL NO. NM0418220-A	
2. NAME OF OPERATOR Devon Energy Corporation (Nevada)				6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA	
3. ADDRESS AND TELEPHONE NO. 20 North Broadway Suite 1500 Oklahoma City, OK 73102				7. UNIT AGREEMENT NAME NA	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 330' FSL & 330' FEL At top prod. interval reported below same At total depth same				8. FARM OR LEASE NAME, WELL NO. Add "27P" Federal #1	
14. PERMIT NO. 30-015-27106				9. AP WELL NO. 30-015-27106	
15. DATE SPUDDED 11/7/92				10. FIELD AND POOL, OR WILDCAT Ingle Wells Delaware	
16. DATE T.D. REACHED 11/24/92				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Section 27-T23S-R31E	
17. DATE COMPL. (Ready to prod.) 1/7/93				12. COUNTY OR PARISH Eddy	
18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 3452.2'				13. STATE NM	
20. TOTAL DEPTH, MD & TVD 8328'		21. PLUG BACK T.D., MD & TVD 8281'		19. ELEV. CASINGHEAD 3471'	
22. IF MULTIPLE COMPL., HOW MANY* 1				23. INTERVALS DRILLED BY ROTARY TOOLS X CABLE TOOLS	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 7962' - 8046' Delaware 8102' - 8164' Delaware				25. WAS DIRECTIONAL SURVEY MADE yes - enclosed	
26. TYPE ELECTRIC AND OTHER LOGS RUN Cement Bond Log Dual Laterolog Micro-SFL Gamma Ray, Compensated Neutron Density				27. WAS WELL CORRED NO	
28. CASING RECORD (Report all strings set in well)					
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48ppf	849'	17 1/2"	650 sks. (cir'd to surf)	none
8 5/8"	32 ppf	4350'	11"	2200 sks. (cir'd to surf)	none
5 1/2"	5.5 & 17 ppf	8328'	5 1/2"	1150 sks. TOC = 2500'	none
29. LINER RECORD					
SIZE	TOP (MD)	BOTTOM (MD)	BACKS CEMENT*	SCREEN (MD)	
30. TUBING RECORD					
SIZE	DEPTH SET (MD)	PACKER SET (MD)			
2 7/8"	7951'	7951'			
31. PREPARATION RECORD (Interval, size and number)					
7962' - 8046' (84 holes) 8102' - 8164' (62 holes)					
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.					
DEPTH INTERVAL (MD)			AMOUNT AND KIND OF MATERIAL USED		
7962' - 8046'			2500 g. 15% HCl, 59,270 g. Gellec		
			Water + 59,000 # 20/40 sand		
8102' - 8164'			2000 g. 15% HCl, 39,700 g. Gellec		
			Water + 38,000 # 20/40 sand		
33. PRODUCTION					
DATE FIRST PRODUCTION 1/7/93		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) flowing			WELL STATUS (Producing or shut-in) producing
DATE OF TEST 1/12/93	HOURS TESTED 24	CHOKE SIZE 18	PROD'N. FOR TEST PERIOD OIL—BBL. 143	GAS—MCF. 20	WATER—BBL. 30
FLOW. TUBING PRESS. 220		CASING PRESSURE 1000	CALCULATED 24-HOUR RATE OIL—BBL. 143	GAS—MCF. 20	WATER—BBL. 30
					OIL GRAVITY-API (CORR.) 140:1
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) to be connected to NGPL system approximately 1/20/93					
35. LIST OF ATTACHMENTS Slope surveys, logs (3)					
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records					
SIGNED		TITLE Engineering Technician		DATE 1/13/92	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof, cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Rustler	986'					
Delaware	4354'					
Cherry Canyon	5507'					
Brushy Canyon	6930'					
Bone Springs	8214'					

38.

GEOLOGIC MARKERS

NAME	TOP	
	MEAS. DEPTH	TRUE VERT. DEPTH