## RECEIVED

Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

JUN - 6.'94

O. C. D.

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No. NM-0281482-A

6. If Indian, Allottee or Tribe Name

(Note: Report results of multiple completion on Well

SUNDRY NOTICES AND DEPORTS ON WELLS	O. W. D.
SUNDRY NOTICES AND REPORTS ON WELLS	ARTESIA, OFFICE
rm for proposals to the	ARTESIA, OFFICE

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well Oil Well 8. Well Name and No. 2. Name of Operator Mobil Federal No. 7 Pogo Producing Company 9. API Well No. 3. Address and Telephone No. 30-015-27115 P.O. Box 10340, Midland, Texas 79702-7340 (915)682-6822 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Sand Dunes W., Delawar 11. County or Parish, State 330' FSL & 660' FEL, Section 29, T-23-S, R-31-E Eddy Co., New Mexico CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Conversion to Injection & Prod.Casing Dispose Water

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. Completion or Recompletion Report and Log form ) give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 7-7/8" hole to 8110', T.D. Reached @ 21:30 hrs., CDT, September 12, 1992 Western Atlas Logged, ran 5-1/2" 17# & 15.5# casing. Guide Shoe @ 8110', Float collar @ 8063', Stage tool @ 6176'. Western cemented 1st stage with 505 sx "H" with 3% KCL. Plugged down and tool opened with 1100 psig. circ'd 6-1/2 hrs. between stages. Cemented 2nd stage with 550 sx PSL "C" mixed 12.4 ppg. Tailed with 200 sx "C" neat mixed 14.8 ppg. Plugged down & tool closed with 2700 psig Job completed 09:00 hrs. CDT, September 15, 1992. TOC 3200' as per CBL ran September 19, 1992.

14. I hereby certify that the foregoing is true and correct Signed Line And Willed	Title _	Division Operati	ions Manager	Date	Oct. 5, 1992
(This space for Federal or State office use)					
Approved by Conditions of approval, if any:	Tide _			Date	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements