

## FIELD REPORT FOR CEMENTING OF WELLS

## OIL CONSERVATION DIVISION

Operator YATES PETROLEUM CORP		Lease PAULINE "ALB" STATE		Well # 8	
Location of Well	Unit L	Section 32	Township 23	Range 31	County EDDY
Drilling Contractor	Undesignated		Type of Equipment Rotary		

APPROVED CASING PROGRAM

\* *Witness*

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2	* 13 3/8	54.5#		500	700 Circ
11	* 8 5/8	32#		4200'	2800 Circ
7 7/8	* 5 1/2	17# & 15.5#		8200 TD	800

Casing Data:

Surface 11 joints of 13 3/8 inch 54 # Grade J55  
(Approved) (Rejected)

Inspected by \_\_\_\_\_ date \_\_\_\_\_

Cementing Program

Size of hole 17 1/2 Size of Casing 13 3/8 Sacks cement required 500

Type of Shoe used Tex Float collar used yes Btm 3 jts welded yes

TD of hole 501 Set 530 Feet of 13 3/8 Inch 54 # Grade J55

(New)-used csg. @ 501 with 250 sacks neat cement around shoe 2% C.C. 1/4 lb. Se/ocel  
+ 250 sax Lite additives 2% C.C. 1 Reported to M. Williams

Plug down @ 1:15 (AM) (PM) Date 3-2-93

Cement circulated yes No. of Sacks 125

Cemented by Western Co. Witnessed by JR

Temp. Survey ran @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_ top cement @ \_\_\_\_\_

Casing test @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method Used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Checked for shut off @ \_\_\_\_\_ (AM) (PM) Date \_\_\_\_\_

Method used \_\_\_\_\_ Witnessed by \_\_\_\_\_

Remarks: \_\_\_\_\_