

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Santa Fe Energy Operating Partners, L.P. ✓

3. Address and Telephone No.

550 W. Texas, Suite 1330, Midland, TX 79701 (915) 687-3551

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

(A), 660' FNL and 330' FEL, Sec. 17, T-23S, R-31E

5. Lease Designation and Serial No.

NM-45235

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Pure Gold C-17 Federal #5

9. API Well No.

30-015-27392

10. Field and Pool, or Exploratory Area

Sand Dunes, West (Delaware

11. County or Parish, State

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Ran casing string

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5/11/93: Depth 4085'. RU and run 102 jts 8-5/8" 32# K-55 LT&C casing and set at 4084'. FC at 4008'. Cemented w/ 1600 sx Cl "C" Lite + 9 pps salt, 1/4 pps Celloflake. Tail w/ 500 sx Cl "C" + 2% CaCl<sub>2</sub>. Plug down at 11:35 p.m. CST. Circ 175 sx to pit. WOC.

5/12/93: Cut off and weld on head. NU and test BOP's and manifold to 3000 psi. Test Hydril to 1500 psi - okay. TIH. WOC total of 24 hours. Test casing to 1500 psi.

5/13/93: Resume drilling operations.

14. I hereby certify that the foregoing is true and correct

Signed

*Darryl McCullough*

Title Sr. Production Clerk

Date May 14, 1993

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

Date