

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 19601

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Union 35 Federal #5

9. API Well No.

30-015-27435

10. Field and Pool, or Exploratory Area

Herradura Bend Delaware

11. County or Parish, State East

Eddy, NM

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

HANLEY PETROLEUM INC.

3. Address and Telephone No.

415 W. Wall, Suite 1500, Midland, TX 79701 915/684-8051

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

630' FNL & 2010' FWL of Sec. 35, T-22-S, R-28-E, NMPM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spudding & Surf. Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 6/1/93 MIRU Peterson Rig #2. Spudded 12 1/4" hole @ 1:30 P.M. 5/31/93. Reached T.D. of 462' @ 7:15 P.M. Ran 10 jts. 8 5/8" casing. Set @ 461'. Halliburton cemented w/370 sx Class C w/2% CaCl<sub>2</sub>, 1/4" flocele & 5" gilsonite. Circulated 165 sx to pit.
- 6/2/93 NU BOP's & tested all BOP equipment & casing to 1500 psi. Started drilling 7 7/8" hole @ 7:00 P.M. 6/1/93.
- 6/3/93 Drilling @ 1610' in Anhydrite. MW 10, Vis 28, pH 10. Dev.Sur. 1 1/2" @ 941', 1 3/4" @ 1158' 2" @ 1402', 1 1/2" @ 1601'.
- 6/4/93 Drilling @ 2310' in Anhydrite & salt. MW 10, Vis 28, pH 10. Dev.Sur. 1" @ 1785', 2 1/2" @ 1970', 1 1/2" @ 2062'.
- 6/5/93 Drilling @ 3264' in sand & shale. MW 10, Vis 28, pH 10, Dev. Sur. 2 1/2" @ 2313', 2 1/2" @ 2488', 2" @ 3162'.
- 6/6/93 Drilling @ 4224 in sand & shale. MW 10, Vis 28, pH 10, Dev. Sur 1 1/2" @ 3650', 3/4" @ 4150'
- 6/7/93 Drilling @ 5112 in sand & shale, MW 10, Vis 28, pH 10, Dev. Sur. 1" @ 4648'.
- 6/8/93 Drilling @ 5666' in sand & Shale, MW 10, Vis.28, pH 10, Dev. Sur. 1 1/2" @ 5142'.
- 6/9/93 Drilling @ 6090' in sand & shale, MW 10, Vis 28, pH 10, Dev. Sur. 1 1/2" @ 5708'.
- 6/10/93 Drilling @ 6556' in lime & shale, MW 10, Vis 28, pH 10, Dev. Sur. 1 1/2" @ 6191', 1 1/2" @ 6511'

14. I hereby certify that the foregoing is true and correct

Signed Greg Wilkes (This space for Federal or State office use)

Title Chief Engineer

Date 6/10/93

PETROLEUM ENGINEER

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title

Date

J. Lara  
18 1993