

Multi-Point Surface Use and Operations Plan

James Ranch No. 57

Page 3

- B. The ground surface of the location is located among several sand dunes with vegetation growing on them. The location will be constructed by leveling the necessary terrain and covering with at least six inches of compacted caliche.
- C. The reserve pits will be plastic lined.
- D. A 400' x 400' work area which will contain the pad and pit area has been staked and flagged.

10. PLAN FOR RESTORATION OF THE SURFACE

- A. After finishing drilling and/or completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleared of all trash and junk, to leave the wellsite in an aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any, containing fluid will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and/or vegetation requirements of the Bureau of Land Management and the United States Geological Survey will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and levelled within 300 days after abandonment.

11. TOPOGRAPHY

- A. The wellsite and access route are located in a relatively flat area.
- B. The top soil at the wellsite is sandy.
- C. The vegetation cover at the wellsite is moderately sparse with scattered mesquite, prairie grasses, and shinnery oak.
- D. No wildlife was observed but it is likely that deer, rabbits, coyotes, and rodents traverse the area.
- E. There are no ponds, lakes, streams, or rivers within one mile of the wellsite.
- F. There is no evidence of any archaeological, historical, or cultural sites in the vicinity of the location.