

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Pogo Producing Company

3. Address and Telephone No.

P. O. Box 10340, Midland, TX 79702-7340 (915)682-6822

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2280' FNL & 460' FWL, Section 23, T24S, R29E

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-81586

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

River Bend Federal No. 7

9. API Well No.

30-015-27994

10. Field and Pool, or Exploratory Area

Wildcat Bone Spring

11. County or Parish, State

Eddy County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Intermediate Casing
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled 11" hole 465' to 2934'. TD reached @ 1730 hrs CDT 6/4/94. Ran 68 jts 8-5/8", 24# & 32#, J-55 ST&C casing. Guide shoe @ 2934'. Float collar @ 2887'. Howco cemented w/ 1100 sx Halliburton Lite @ 12.7 followed by 200 sx Class "C" + 5 pps salt @ 14.8 ppg. Plug down @ 2887'. Recovered 150 sx excess cement. Set slips & make cut-off Weld on wellhead and test to 1500 psi. NU BOP's and test to 1500 psi.

JUL 24 1995

OIL CON. DIV.
DIST. 2

28 1994

535

14. I hereby certify that the foregoing is true and correct

Signed [Signature]

Title Senior Operations Engineer

Date July 21, 1994

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____