		 NM 03	IL CONS COMMISSION CIST
Form 3160-5 (June 1990)	DEPARTMEN BUREAU OF L SUNDRY NOTICES AN this form for proposals to drill	TED STATES T OF THE INTERIOR AND MANAGEMENT D REPORTS ON WELLS or to deepen or reentry to a different reservoir.	OT DD FORM APPROVED
	SUBMIT	7. If Unit or CA, Agreement Designation	
1. Type of Well    X Oil   Gas   Other   2. Name of Operator			8. Well Name and No.  JAMES E FED. #9
•	s Petroleum Company	9. API Well No. 30-015-28056	
4001 Penbrook Street, Odessa, TX 79762 915/368-1488  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  SHL - UNIT P, 1060 FSL & 10' FEL OF SEC. 11, T-22-S, R-30-E BHL - UNIT P, 982.6 FSL & 330' FEL OF SEC. 11, T-22-S, R-30-E			10. Field and Pool, or exploratory Area CABIN LAKE (DELAWARE)  11. County or Parish, State
			EDDY NM
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA			
TYPE OF SUBMISSION  Notice of Intent		TYPE OF ACTION	Change of Plans
Subsequent Report		Recompletion Plugging Beck	New Construction Non-Routine Fracturing
Final Abandonment Notice		Casing Ropair  Altering Casing  Other Set Surf, Intrm, Pr	Water Shut-Off Conversion to Injection Dispose Water (Note: Report smalls of multiple completion on Wall Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Cloarly mate all pertinent details, and give pertinent dates, including estimated date of marting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)  11/08/94 SPUD 17-1/2" HOLE.  11/09/94 RAN 13-3/8" CSG W/12 JTS 48# K-55, GUIDE SHOE @ 480', FLOAT INSERT @438'. MIX & PUMP 800 SXS CLASS C CMT. CIRC 190 SX TO RESERVE PIT. WOC.  11/11/94 DRILL INSERT FLOAT, TEST 13-3/8" CSG TO 600# PSI FOR 30 MIN., HELD OK. DRILL CMT, DRILLING 12-1/4" HOLE. LOST RETURNS @584'. PUMP 200 SX CLASS C CMT PLUG. WOC.  11/12/94 DRILL CMT & TAGGED @483', FELL OUT OF CMT 591', DRILL FORMATION, LOST CIRC, MIX & PUMP 200 SX CLASS C PLUG, WOC. DRILLING FORMATION.  11/16/94 RAN 9-5/8" CSG W/85 JTS 36# J-55, FLOAT SHOE @3690', FLOAT COLLAR @3641'. PUMP LEAD CMT W/1000 SX CLASS C 65/35 POZ. TAIL W/200 SX CLASS C. CIRC 130 SX CMT TO RESERVE PIT. LOST RETURNS W/CEMENT.  11/17/94 RAN 1" GROUT STRING AND TIH TO 458', GROUTED ANNULUS W/150 SX OF CLASS C NEAT. SET SLIPS, TEST'D, BOP AND RAN GR/NEUTRON LOG.  11/20/94 DRILLED 8-3/4" HOLE TO KOP @5141', RAN GYRO SURVEY AT KOP. DIRECTIONALLY DRILLING.  11/27/94 RAN 7" CSG W/158 JTS 23# & 26# J-55, GUIDE SHOE @6155', FLOAT COLLAR @6107', TOP OF 26# CSG @5085'. CMT LEAD W/250 SX CLASS C & TAIL W/250 SX CLASS C. RAN TEMP. SURVEY, FOUND TOC @2150.			
14. I hereby certi	ify that the foregoing is true and correct	Title SUPERVISOR, REGULATORY AFF	FAIRS Deta 11/30/94
			CCEPTED FOR RECORD
Conditions of approval, if any:			

CARLSBAD, NEW MEXICO