Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

IM OIL CONS COMMISSION Drawer DD

Artesia NM 88210

JOF

Budget Bureau No. 1004-0135 Expires: March 31, 1993

*					i	ires: March 31, 1993	
SUNDRY NOTICES AND REPORTS ON WELLS					5. Lease Designation and Serial No. NM-29233		
Do not use this form for pre	roposals to	drill or to deepen o	r reentry to a diffe	erent reservoir.	6. If Indian, Alottee		
Use "APPLI	ICATION I	FOR PERMIT" fo	r such proposals	·	, o, ii indian, Alottee	or the Name	
	SUBM	IIT IN TRIPLICAT	E		7. If Unit or CA, Ag	reement Designation	
Type of Well: OIL GAS OTHER					8. Well Name and Number  NEFF '13' FEDERAL  9		
Name of Operator TEXACO EXPLORAT ON & PRODUCTION INC.							
Address and Telanhone No.					9. API Well No.		
P.O. Box 46510, Denver Colorado 80201-6510 (303)621-485  Location of Well (Footage, Sec., T., R., M., or Survey Description)					30-015-28125		
Fort From The					10. Field and Pool, Exploratory Area LIVINGSTON RIDGE DELAWARE		
it Letter C : 660 Fe	et Floin i	THE NORTH LINE	and 1900	_ reerrom me	11. County or Pari		
EST Line Section 13		Township 22-S	Range	e 31-E	11. County of Fair	EDDY , NM	
Check Appl	ronriate	Env(s) To In	dicate Natur	re of Notice, Re	eport or Othi	er Data	
TYPE OF SUBMISSION	opnace	- LOX(3) 10 III	aloate Hatul		YPE OF ACTION		
			Abandonment			Change of Plans	
			Recompletion			New Construction	
Notice of Intent			Plugging Back		Ē	Non-Routine Fractu	uring
						Water Shut-Off	-
Subsequent Report		<u> </u>	Casing Repair Altering Casing	ī	H	Conversion to Inject	tion
Final Abandonment Notice		L				•	
		. 🗠	OTHER:	PRODUCTION CS		Dispose Water e: Report results of multiple	romoietion on Well
Describe Proposed or Completed Oper directionally drilled, give subsurface loc	cations and	measured and true ve	ertical depths for al	ll markers and zones pe	ertinent to this work,)	•.	
RAN 153 JOINTS OF 5 1/2, 15.5 #	# K-55 AN	D 46 JOINTS OF 1	7.0# K-55, STC	: CASING SET @ 87 W/ 2% GEL, 5% SA	'47'. LT, 1/4# FLOCEL	E (14.2 PPG, 1.35	CF/S).
. RAN 153 JOINTS OF 5 1/2, 15.5 # . DOWELL CEMENTED IN STAGE CIRCULATED 220 SACKS. DOWELL CEMENTED IN STAGE F/B 100 CLASS H (1.18 PPG, 1.19 PLUG DOWN TIME @ 7:45 AM 12 . ND. RELEASE RIG @ 6:30 PM 12	# K-55 AN E #1 WITH E #2 WITH 9 CF) CIR 2-23-94.	D 46 JOINTS OF 1 750 SACKS 50/50 900 SACKS 35/65	7.0# K-55, STC POZ CLASS H	W/ 2% GEL, 5% SA 6% GEL, 5% SALT.	LT, 1/4# FLOCEL 1/4# FLOCELE(12	.8 PPG, 1.94 CF/S	
. RAN 153 JOINTS OF 5 1/2, 15.5 # . DOWELL CEMENTED IN STAGE CIRCULATED 220 SACKS. DOWELL CEMENTED IN STAGE F/B 100 CLASS H (1.18 PPG, 1.19 PLUG DOWN TIME @ 7:45 AM 12 I. ND. RELEASE RIG @ 6:30 PM 12	# K-55 AN E #1 WITH E #2 WITH 9 CF) CIR 2-23-94.	D 46 JOINTS OF 1 750 SACKS 50/50 900 SACKS 35/65	7.0# K-55, STC POZ CLASS H	W/ 2% GEL, 5% SA 6% GEL, 5% SALT.	LT, 1/4# FLOCEL 1/4# FLOCELE(12	.8 PPG, 1.94 CF/S	
RAN 153 JOINTS OF 5 1/2, 15.5 # DOWELL CEMENTED IN STAGE CIRCULATED 220 SACKS. DOWELL CEMENTED IN STAGE F/B 100 CLASS H (1.18 PPG, 1.19 PLUG DOWN TIME @ 7:45 AM 12 ND. RELEASE RIG @ 6:30 PM 12 PREP TO COMPLETE.	# K-55 AN : #1 WITH E #2 WITH 9 CF) CIR 2-23-94. 2-23-94.	D 46 JOINTS OF 1 750 SACKS 50/50 900 SACKS 35/65 CUILATED 50 SAC	7.0# K-55, STC POZ CLASS H POZ CLASS H RKS THEN LOST	W/ 2% GEL, 5% SALT. F CIRCULATION W	LT, 1/4# FLOCELE(12/25 BBLS FLUSH	.8 PPG, 1.94 CF/S REMAINING.	5).
RAN 153 JOINTS OF 5 1/2, 15.5 # DOWELL CEMENTED IN STAGE CIRCULATED 220 SACKS. DOWELL CEMENTED IN STAGE F/B 100 CLASS H (1.18 PPG, 1.19 PLUG DOWN TIME @ 7:45 AM 12 ND. RELEASE RIG @ 6:30 PM 12 PREP TO COMPLETE.	# K-55 AN #1 WITH #2 WITH 9 CF) CIR 2-23-94. 2-23-94.	D 46 JOINTS OF 1 750 SACKS 50/50 900 SACKS 35/65 CUILATED 50 SAC	7.0# K-55, STC POZ CLASS H POZ CLASS H RKS THEN LOST	W/ 2% GEL, 5% SA 6% GEL, 5% SALT.	LT, 1/4# FLOCELE(12/25 BBLS FLUSH	.8 PPG, 1.94 CF/S REMAINING.	
DOWELL CEMENTED IN STAGE F/B 100 CLASS H (1.18 PPG, 1.19	# K-55 AN #1 WITH #2 WITH 9 CF) CIR 2-23-94. 2-23-94.	D 46 JOINTS OF 1 750 SACKS 50/50 900 SACKS 35/65 CUILATED 50 SAC	7.0# K-55, STC POZ CLASS H POZ CLASS H RKS THEN LOST	W/ 2% GEL, 5% SALT. F CIRCULATION W	LT, 1/4# FLOCELE(12/25 BBLS FLUSH	.8 PPG, 1.94 CF/S REMAINING.	5).