

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMBER
OF COPIES REQUIRED

OIL CONSERVATION
COMMISSION
Form No. 3160-3

(See instructions on
reverse)

Artesia, NM 88210
BASIC DESIGNATION AND SERIAL NO.

NM-0556859

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: ☒ OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF. GENV. ☐ OTHER

2. NAME OF OPERATOR: Strata Production Company

3a. Area Code & Phone No.
505-622-1127

3. ADDRESS OF OPERATOR:

P.O. Box 1030, Roswell, New Mexico 88202-1030

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements):

At surface 1650' FNL & 990' FWL

At top prod. interval reported below

At total depth

9a. API Well No. 30-015-28272

14. PERMIT NO. DATE ISSUED
15. DATE SPUNDED 7/31/95 16. DATE T.D. REACHED 8/15/95 17. DATE COMPL. (Ready to prod.) 10/18/95 18. ELEVATIONS (OF, RKR, RT, GR, ETC.) 2986' GR 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 7100' 21. PLUG BACK T.D., MD & TVD 7070' 22. IF MULTIPLE COMPL., HOW MANY? 23. INTERVALS DRILLED BY 0-7100' ROTARY TOOLS CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD) 6654'-6801' Delaware 25. WAS DIRECTIONAL SURVEY MADE Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN CNL/LDT, DLL/MSFL 27. WAS WELL CORED Sidewall

CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8"	48#	315'	17 1/2"	425 sacks Class "H"	130 sacks
8 5/8"	32#	3020'	11"	700 sacks Poz "C"; 200 sacks Cl "C"	156 sacks
5 1/2"	17#	7100'	7 7/8"	1185 sacks Poz "H"	256 sacks

LINER RECORD					TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	6720'	

31. PERFORATION RECORD (Interval, size and number)			32. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
6654'-6703'	27	.42 holes	DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
6755'-6801'	14	.42 holes	6654'-6703'	Acid 2500 gal 7 1/2% NEFE
			6755'-6801'	Acid 1500 gal 7 1/2% NEFE
				Frac 226,880# 16/30 Jordan sand

PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)
10/18/95		Flowing					Producing
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
10/25/95	24	24/64"		236	384	481	1627/1
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
	1500#		236	384	481	41.7	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

Sold

35. LIST OF ATTACHMENTS

Deviation Survey, CNL/LDT, DLL/MSFL

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Carol J. Garcia

TITLE Production Records Manager

DATE

11/6/95

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Rustler Salado Castile Bell Canyon Cherry Canyon Brushy Canyon T/Bone Spring	Surface 255' 1760' 3124' 3993' 5188' 6840'	255' 1760' 3124' 3993' 5188' 6840' TD	Redbed & Salt Salt & Anhydrite Anhydrite Sandstone Sandstone & Shale Sandstone & Shale Limestone			