

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD FORM APPROVED
Artesia, NM 88210
Expires: March 31, 1993

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
YATES PETROLEUM CORPORATION (505) 748-1471

3. Address and Telephone No.
105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1980' FSL & 1980' FWL of Section 15-T23S-R24E (Unit K, NESW)

5. Lease Designation and Serial No.
NM-92744

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.
Robinia Draw Unit #1

9. API Well No.
30-015-28622

10. Field and Pool, or Exploratory Area
Eddy Undes. Group 7

11. County or Parish, State
Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Surface casing & cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 17-1/2" hole with rotary tools at 6:15 AM 10-2-95.

TD 347'. Reached TD at 5:45 PM 10-2-95. Ran 8 joints of 13-3/8" 54.5# 8rd J-55 ST&C (350.85') of casing set at 347'. 1-Texas Pattern notched guide shoe set at 347'. Insert float set at 302'. Cemented with 350 sacks Class C 2% CaCl₂ (yield 1.32, weight 14.8). PD 10:00 PM 10-2-95. Bumped plug to 500 psi, OK. Circulated 97 sacks. WOC. Cut off and weld on flow nipple. Drilled out at 5:30 PM 10-3-95. WOC 19 hours and 30 minutes. Reduced hole to 12-1/4". Resumed drilling.

14. I hereby certify that the foregoing is true and correct

Signed Rusty Klein Title Production Clerk

Date Oct. 5, 1995

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: