

PAGE START DATE: 5/ 7/96
PAGE START TIME: 9:31: 6
DATA FILE: 3

DELTA TIME HRS	DEPTH FEET	TEMPERATURE 'F	COMMENTS
0.000	1500.00	84.00	
0.667	3760.00	92.00	BREAK
0.683	3805.00	102.75	
0.692	3827.00	102.00	
0.700	3850.00	103.25	
0.717	3897.00	102.50	
0.750	3990.00	105.75	
0.767	4039.00	105.00	
0.783	4088.00	108.25	
0.800	4137.00	104.00	
0.817	4188.00	105.75	
0.833	4238.00	105.00	
0.850	4288.00	109.50	
0.883	4392.00	105.00	
0.917	4495.00	109.00	
0.967	4658.00	107.75	
0.983	4715.00	109.00	
1.033	4886.00	108.50	
1.058	4973.00	109.50	
1.067	5002.00	108.50	
1.100	5122.00	110.75	
1.108	5152.00	110.00	
1.117	5181.00	111.50	
1.133	5241.00	110.50	
1.150	5303.00	113.50	
1.167	5367.00	112.25	
1.183	5431.00	115.25	
1.200	5494.00	113.25	
1.217	5557.00	116.50	
1.250	5690.00	114.50	
1.350	6120.00	122.25	
1.367	6195.00	121.50	
1.400	6348.00	125.75	
1.408	6388.00	124.50	
1.433	6510.00	126.50	
1.450	6593.00	126.25	
1.458	6634.00	128.25	
1.483	6763.00	125.50	
1.517	6940.00	129.25	
1.550	7122.00	128.00	
1.567	7180.00	132.00	M.D.R.

DATE AND TIME CEMENT JOB COMPLETE:

MAY 6, 1996 @ 8:45 PM

DATE AND TIME SURVEY MADE:

MAY 7, 1996 @ 9:45 AM

AMOUNT AND TYPE OF CEMENT USED:

350 SACKS HALLIBURTON LIGHT,
450 SACKS PREMIUM PLUS 50:50
POSMIX RUN BEHIND 7240 FEET OF
5½" CASING IN A 7-7/8" HOLE.

DEPTH FIGURED FROM:

GROUND LEVEL