

F. H. STATE "28" COM #2

1980' FSL & 1650' FWL SEC 28 T23S R26E

EDDY CO N.M.

DRILLED 12/96

13 3/8" 48" @ 615' / CMT W/ 500 SK /
615' CMT CIRC

1798' 9 5/8 40" J-55 @ 1798' / CMT W/ 900 SK / CIRC

TOC: 2946'

TUBING: 2 3/8" N-80 (JT COUNT NOT AVAILABLE) 395

PERFS: 3592-3604' (13 HOLES)

CMT RETAIN @ 4190'

PERF 4245' / CMT W/ 300 SK

CIBP @ 4850' CAP W/ 20' CMT

PERFS: 4968-26' (19 HOLES)

CIBP @ 5075' CAP W/ 20' CMT

PERFS: 5100-03, 16-22, 30-42, 50-54 (28 HOLES)

DV TOOL @ 7479' / CMT W/ 1025 SK / ORIG TOC 4290'

CIBP @ 7865' CAP 20' CMT

PERFS 10282-89; 10296-306, 10416-64 (68 HOLES) 5027

CIBP: 10845' CAP W/ 20' CMT

PERFS: 10914-26 & 10866-95 (18 HOLES)

CIBP @ 11350' CAP W/ 20' CMT

PERFS: 11369-11388 (77 HOLES)

CIBP @ 11500' CAP 20' CMT

PERF: 11576-36; 11540-55, 11560-73 (51 HOLES TOTAL)

7" 23" & 26" S-95 @ 1200' / CMT W/ 885 SK
CIRC'D TO DV TOOL

12008