Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil C 3. Division
811 S. 1st Street FORM APPROVED
Budget Bureau No. 1004-0135

ili o. ist otteet j			Budget Bureau No. 1004-01			
rtesia	NM	88210-2	834	Expires:	March 31.	1993
.,,	14141	DEC	S. Lease	e Designa	tion and Ser	ial No

SUNDRY NOTICES A	ND REPORTS ON WELLS	RFC	NM-45236	
Do not use this form for proposals to drill			32 Milliottee or Tribe Name	
	IN TRIPLICATE		7. If Unit or CA, Agreement Designation	
1. Type of Well X Oil Gas Other		- Comment of the Comm	8. Well Name and No.	
2. Name of Operator Santa Fe Energy Resources, Ir	nc .	DEC 27 '96	-Sterling Silver <u>"33" Fed. #</u> 15	
3. Address and Telephone No. 550 W. Texas, Suite 1330, Midl			9. API Well No. 30 - 015 - 29275	
4. Location of Well (Footage, Sec., T., R., M., or Survey D. 1980' FNL & 990' FEL, Sec. 3	escription)	ARTESIA, OFFICE	10. Field and Pool, or exploratory Area Sand Dunes, W. (Delaware) 11. County or Parish, State Eddy NM	
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE (OF NOTICE, REPORT,		
TYPE OF SUBMISSION				
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Ran casing string		Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well	
13. Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vertical state and true vertical states are subsurfaced or Completed Operations (Clearly state all give subsurface locations and measured and true vertical states).	pertinent details, and give pertinent dates, cal depths for all markers and zones pertin p.m. MST. Depth 4128	on to this work.)	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled,	
12/17/96: RU and ran 102 jts 8 Cemented w/ 950 sx Cl "C" 50:50 Cl "C" + 2% CaCl2. Plug down a hydril and cut csg off. Weld o	-5/8" 32# J-55 LT&C c POZ w/10% gel, 5% sa t.8:00 a.m. MST . Cir	asing and set at lt, and 1/4 pps	[] a a a] a T = 1 / 000	
12/18/96: NU BOP, hydril and m bit and DC's. Test pipe rams & Resume drilling operations.	anifold. Test blind manifold to 1820 psi	rams to 1820 psi for 30 min., ok	for 30 min., ok. TIH w/ . WOC total of 24 hours.	
<u>.</u>	ACCEPTED FOR	1996 ars		
14. Libereby certify that the foregoing in true and correct Signed 1884 (1880)	gh Title Sr. Producti	on Clerk	Date 12/19/96	
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title		Date	