

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 330' FWL of Section 13-T24S-R29E (Unit L, NWSW)

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

NM-88136

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Corral Draw AQH Fed #1

9. API Well No.

30-015-29396

10. Field and Pool, or Exploratory Area

Pierce Crossing Bone Spring,

11. County or Parish, State

East

Eddy Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Resume drilling, surface casing & cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Resumed drilling a 14-3/4" hole with rotary tools at 10:45 PM 3-11-97.

TD 454'. Reached TD at 9:00 AM 3-12-97. Ran 11 joints of 11-3/4" 42# H-40 ST&C (457.14') of casing set at 454'. 1-Texas Pattern notched guide shoe set at 454'. Insert float set at 411'. Cemented with 100 sacks Thixadd, 1/2#/sack celloflake and 10#/sack gilsonite (yield 1.51, weight 14.6) and 105 sacks 65-35-6 "C", 1/43/sack celloflake and 2% CaCl2 (yield 1.87, weight 12.7). Tailed in with 200 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.6). PD 2:30 PM 3-12-97. Bumped plug to 800 psi, OK. Circulated 109 sacks. WOC. Nipped up and tested to 1500 psi, OK. Drilled out at 6:00 AM 3-13-97. WOC 15 hours and 30 minutes. Reduced hole to 11". Resumed drilling. NOTE: Cement job witnessed by Gene Hunt w/BLM-Carlsbad.

ACCEPTED FOR RECORD

MAR 20 1997

acs

RECEIVED

MAR 19 '97

ROSWELL, NM

14. I hereby certify that the foregoing is true and correct

Signed

Title Operations Technician

Date March 14, 1997

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: