

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division

811 S. 1st St.
Artesia, NM 88210

FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

RECEIVED
BUREAU OF LAND MGMT.
ROSWELL OFFICE
AUG 10 1997

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

YATES PETROLEUM CORPORATION

(505) 748-1471

3. Address and Telephone No.

105 South 4th St., Artesia, NM 88210

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2310' FSL & 330' FWL of Section 13-T24S-R29E (Unit L, NWSW)

5. Lease Designation and Serial No.

NM-88136

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Corral Draw AQH Fed #1

9. API Well No.

30-015-29396

10. Field and Pool, or Exploratory Area

Pierce Crossing Bone Spring

11. County or Parish, State

EAST

Eddy Co., NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☒ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Squeeze Bone Springs
perfs & recomplete to
Delaware

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Current Perforations: 9017-9070' and 8042-8165' (Bone Springs):

Propose to cement squeeze perforations 8042-8165' (Bone Springs) by setting a cement retainer at approximately 8025' and squeezing with 100 sacks Class H and 4/10% fluid loss followed by 50 sacks Class H Neat. WOC. Will drill out retainer and pressure test squeezed perforations 8042-8165'.

Will then recomplete uphole to the Delaware as follows:

1. A RBP will be set above perforations 9017-9070' (Bone Springs) and tested.
2. Perforate 6005-6832' (Brushy Canyon), stimulate as necessary for production.
3. Pump test.
4. If decision is made to commingle Brushy Canyon and Bone Springs, a commingling application will be sent to the BLM and the OCD-Santa Fe.

14. I hereby certify that the foregoing is true and correct

Signed

Rusty Glass

Title Operations Technician

Date Aug. 4, 1997

(This space for Federal or State office use)

Approved By (ORIG. SCD) DAVID R. GLASS

Title

PETROLEUM ENGINEER

Date

AUG 18 1997

Conditions of approval, if any: