


District I  
PO Box 1980, Hobbs, NM 88241-1980  
District II  
811 South First, Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

CISF  
BLM  
ST 60

Form C-101  
Revised October 18, 1994  
Instructions on back  
Submit to Appropriate District Office  
State Lease - 6 Copies  
Fee Lease - 5 Copies



AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUG BACK OR ADD A ZONE

Operator Name and Address. Nadel and Gussman Permian, L.L.C. 601 N. Marienfeld, Suite 508 Midland, TX 79701		OGRID Number 155615
Property Code 24354		Property Name Rolling Rock State
Well No. 1		

7 Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
4	31	23S	25E		990'	South	990'	West	Eddy

8 Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
Proposed Pool 1 Baldrige Canyon (Morrow)					Proposed Pool 2 Dark Canyon (Morrow)				

Work Type Code N	Well Type Code G	Cable/Rotary Rotary	Lease Type Code S	Ground Level Elevation 3875'
Multiple No	Proposed Depth 10,800'	Formation Morrow	Contractor NA	Spud Date +/- 4/15/99

Minimum WOC time 18 hrs 21 Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/2"	13 3/8"	48	400'	Circ	Surface
12 1/4"	8 5/8" B6A	36	2700'	Circ	Surface
7 7/8"	5 1/2"	17	10,800'	2800'	8000'
				Post TD - 1	
				3-19-99	

22 Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Drill and complete well in Morrow with a projected TD of 10,800'. A BOP schematic is attached. A DV tool may be used if zones above the Morrow are prospective. The Morrow will be completed by using thru-tubing or tubing conveyed guns. A 5000 psig tree will be nipples up prior to perforating.

Appr. 3/10/99

NSL - 4228

Notify N.M.O.C.C. in sufficient  
time to witness cementing  
the 8 5/8" casing

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. Signature: <i>John D. Rodgers</i> Printed name: John D. Rodgers Title: Engineer Date: 3/8/99		OIL CONSERVATION DIVISION Approved by: ORIGINAL SIGNED BY TIM W. GUM DISTRICT II SUPERVISOR Title: <i>BA</i> Approval Date: 3-12-99 Expiration Date: 3-12-00 Conditions of Approval: Attached <input type="checkbox"/>	
---	--	---	--