

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO. 30-015-30588
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. VB0528
7. Lease Name or Unit Agreement Name Rolling Rock State
8. Well No. 1
9. Pool name or Wildcat Baldrige Canyon Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER ☐	
2. Name of Operator Nadel and Gussman Permian, L.L.C.	
3. Address of Operator 601 N. Marienfeld, Suite 508, Midland, TX 79701	
4. Well Location Unit Letter <u>M</u> : <u>990</u> Feet From The <u>South</u> Line and <u>990</u> Feet From The <u>West</u> Line Section <u>31</u> Township <u>23S</u> Range <u>25E</u> NMPM <u>Eddy</u> County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3875' Ground Level	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☒
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☒
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4/22/99 - Spud @ 12:00am MDST by Patterson Drilling Co. Rig #78.
4/23/99 - Set 13 3/8" 48#/ft H-40 ST&C csg at 402'. Cmt w/200 sx class H Thickset + 150 sx Class C (6% gel) + 150 sx Class C. Plug down @ 3:00am 4/23/99. Cmt did not circ. Tag cmt @ 137' w/ 1" pipe. Cmt from top w/150 sx Class C w/2% CACl₂. WOC. Tag cmt @ 125'. Cmt from top w/50 sx Class C w/3% CACl₂. WOC. Tag cmt @ 119'. Cmt from top w/50 sx Class C w/3% CACl₂. WOC. Tag cmt @ 100'. Cmt from top w/ 100sx Class C w/4% CACl₂ while dropping 7 yards pea gravel from top. Circ. 20 sx cmt. WOC for 18 1/2 hrs. Tested csg to 1500 psi for 30 minutes. Held ok.
4/28/99 - Set 8 5/8" 32#/ft J-55 LT&C casing at 2723'. Cmt w/150 sx Class H + 1000 sx Poz (6% gel) + 150 sx Class C. Circ. 213 sx to surface. WOC for 28 hours. Pressure test csg to 1200 psi for 30 minutes. Held ok.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE John D. Rodgers TITLE Operations Engineer DATE 4/29/99
TYPE OR PRINT NAME John D. Rodgers TELEPHONE NO. 915/682-4429

(This space for State Use)

APPROVED BY Jim W. Gamm B60 DISTRICT SUPERVISOR Jim W. Gamm DATE 5-6-99
CONDITIONS OF APPROVAL, IF ANY: