Submit 3 Copies to Appropriate District Office

State of New Mexico Engy, Minerals and Natural Resources Department

015F	
L' Un	
- 1/	

Form C-103 Revised 1-1-89

OIL CO	ONSERVATION DIVISION P.O. Box 2088
San	P.O. Box 2000 ta Fe. New Mexico 87504-2088

	OIL CONSERVATION	ON DIVISION	WELL API NO.	
DISTRICTI P.O. Box 1980, Hobbs, NM 88240	P.O. Box 2088		30-015-30757	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504-2088	5. Indicate Type of Lease STATE X FEE	
DISTRICT III 1000 Rio Brazos Rd., Azzec, NM 87410	7.40		6. State Oil & Gas Lease No. V-4858	
(DO NOT USE THIS FORM FOR PE	TICES AND REPORTS ON WE ROPOSALS TO DRILL OR TO DEERE ERVOIR. USE "APPLICATION FOR P C-101) FOR SUCH PROPOSALS.)		7. Lease Name or Unit Agreement Name	
1. Type of Well: OR. WELL WELL [K ones	7 C. V.	Opuntia Draw ATG State Com	
2 Name of Operator V YATES PETROLEUM CORPO		11.91.81.4	8. Well No. 1 9. Pool name or Wildcat	
3. Address of Operator 105 South 4th St., Ar	rtesia, NM 88210		Und. Baldridge Canyon Morrow	
4. Well Location Unit Letter M : 1090 Feet From The South Line and 660 Feet From The West Line				
Section 29 Township 23S Range 25E NMPM Eddy County 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3818' GR				
Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSECUENT REPORT OF:				
11. Chec	k Appropriate Box to indicate NTENTION TO:	SUI	BOLGOLITI TILL STORE	
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING	
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLIN		
PULL OR ALTER CASING]	CASING TEST AND	conductor, resume drilling, X	
OTHER:		- I GUTTACE	Casing a comme	
OTHEM:				

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed

Spudded a 12-3/4" hole with rat hole machine at 12:00 PM 10-21-99. Drilled to 40'. Reamed 12-3/4" hole to 26" hole from 0-38'. Set 20" conductor pipe at 38' and cemented to surface. NOTE: Notified Mary Ann w/OCD-Artesia of spud. Resumed drilling a 17-1/2" hole with rotary tools at 7:00 AM 10-24-99.

TD 412'. Reached TD at 5:15 PM 10-25-99. Ran 9 joints of 13-3/8" 48# H-40 8rd ST&C (415.77') of casing set at 412'. 1-Texas Pattern notched guide shoe set at 412'. Insert float set at 367'. Cemented with 200 sacks Thixadd, 1/4#/sack celloseal, 10#/ sack gilsonite (yield 1.53, weight 14.6) and 150 sacks BJ Lite and 2% CaCl2 (yield 1.34,

	Operations Technician DATE Oct. 29, 1999
10 Tacked cement at 200 · Spoccou 25	CONTINUED ON NEXT PAGE:
with 4% CaCl2. PD 4:15 RM 10 20 20 20 20 20 20 20 20 20 20 20 20 20	PD 7:45 AM 10-26-99. WOC 1-1/2 hours. Ran sacks Class C with 4% CaCl2. PD 10:00 AM CONTINUED ON NEXT PAGE:
WOC 4 hours. Rail 1 . 1000	n = 1" Tagged Cement at 213 .
. 1, 1, Q) Ph 1:30 PM 10-23-33.	control 25 sacks Class C
Insert float set at 307. Communication in the sack gilsonite (yield 1.53, weight 14.6)	and 150 sacks be 22-1-1
Theart float set at Joy	1 150 cacke RI life and 26 Cacia ()

Rusty Klein TYPE OR PRINT NAME (This space for State Use) ORIGINAL SIGNED BY TIM W. GUM

DISTRICT H SUPERVISOR

APPROVED BY-CONDITIONS OF APPROVAL, IF ANY: