

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally verticle depths shall be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. Th filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION

Southeastern New Mexico

Northwestern New Mexico

T. Anhy		T. Canyon	T. Ojo Alamo	T. Penn "
T. Salt	320	T. Strawn	T. Kirtland-Fruitland	T. Penn "C
B. Salt	1730	T. Atoka	T. Pictured Cliffs	T. Penn "
T. Yates		T. Miss	T. Cliff House	T. Leadvi
T. 7 Rivers		T. Devonian	T. Menefee	T. Madiso
T. Queen		T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg		T. Montoya	T. Mancos	T. McCrac
T. San Andres		T. Simpson	T. Gallup	T. Ignacio
T. Glorieta		T. McKee	T. Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	T
T. Blinbry		T. Gr. Wash	T. Morrison	T
T. Tubb		T. Delaware Sand	T. Todilto	T
T. Drinkard		T. Bone Springs	T. Entrada	T
T. Abo		T.	T. Wingate	T
T. Wolfcamp		T	T. Chinle	T
T. Penn		T	T. Permian	T
T. Cisco (Bough C)		T	T. Penn "A"	T

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 3, from	to
No. 2, from	to	No. 4, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in the hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	
0	245	245	ANHYDRITE				
245	320	75	SALT				
320	1730	410	ANHYDRITE, SALT				
1730	3282	1552	LIMESTONE				
3282	3312	30	SANDSTONE				
3312	4078	766	SANDSTONE				