

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NM Oil Cons. Division
311 S. 1st Street
Albuquerque, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
5. Lease Designation and Serial No
NM-0540701

Do not use this form for proposals to drill or to deepen or to enter to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
Oil Well ☒ Gas Well ☐ Other ☐
2. Name of Operator
Mewbourne Oil Company
3. Address and Telephone No.
PO Box 5270, Hobbs, N.M. 88240 505-393-5905
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
660' FNL & 660' FEL
Sec. 18 T-23S R-27E



6. If Indian, Allottee or Tribe Name
7. If Unit or CA, Agreement Designation
8. Well Name and No.
Ranch Hand 18 Federal Com #2
9. API Well No.
30-015-31075
10. Field and Pool, or Exploratory Area
Carlsbad, South Morrow
11. County or Parish, State
Eddy, N M

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent
- ☒ Subsequent Report
- Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- Change of Plans
- New Construction
- Non-Routine Fracturing
- Water Shut-Off
- Conversion to Injection
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

6/10/2000...TD'ed 8 3/4" hole @ 12150'. Ran Open hole logs.

6/14/2000...Called BLM for Plugging orders & Plugged as listed below:

11382-11582'	(200')	85 sks H w/ .4% FL-52	15.6#/gal & 1.18 yd
10443-10643'	(200')	90 sks H w/ .4% FL-52	15.6#/gal & 1.18 yd
8875-9025'	(200')	65 sks H w/ .4% FL-52	15.6#/gal & 1.18 yd
5600-5700'	(100')	40 sks C Neat	14.8#/gal & 1.32 yd
2633-2733'	(100')	45 sks C w/ 3% CaCl ₂	14.8 3/gal & 1.32 yd --TAGGED @ 2608'
458-558'	(100')	35 sks C Neat	14.8#/gal & 1.32 yd
50' to Surface	(50')	15 sks C Neat	14.8#/gal & 1.32 yd

ND well head & install DH Marker.
P&A'ed completed 6/15/2000 @ 6:00 am.

Approved as to plugging of the well ~~form~~
and the condition is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed

Title N M Young District Manager

Date 06/22/00

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

DAVID R. GLASS

Title

PETROLEUM ENGINEER

Date

JUL 03 2000