

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO.

30-015-31913

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

V-2705

7. Lease Name or Unit Agreement Name:

Graham AKB State

7. Well No.

#8

8. Pool name or Wildcat

Lost Tank Delaware

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street Artesia, NM 88210

4. Well Location

Unit Letter E : 1650 feet from the North line and 330 feet from the West line

Section 2 Township 22S Range 31E NMPM Eddy County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3514' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: run intermediate casing ☒

Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/3/02 - Reached TD of intermediate 11" hole at 4105' at 12:30 PM.

Ran 96 joints (4114.45') 8-5/8" 32# J-55 casing set at 4105'.

Float shoe set at 4105'. Float collar set at 4061.29'.

Cemented with 1250 sxs Class C (35:65:6) + 2% CaCl₂ + .25 pps celloflake + 5 pps gilsonite (yld 1.98, wt 12.5).

Tailed in with 250 sxs C + 2% CaCl₂ (yld 1.34, wt 14.8).

5/4/02 - PD at 12:30 AM. Bumped plug to 2000#, held OK. Circ 28 sxs. WOC.

Jerry Guy with NMOCD witnessed job.

5/5/02 - Drilled out at 1:15 AM. WOC 24 hours 45 mins. Reduced hole to 7-7/8" and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Susan Herpin TITLE Engineering Technician DATE May 9, 2002

Type or print name Susan Herpin

Telephone No. 505-748-1471

(This space for State use)

ORIGINAL SIGNED BY TIM W. GUM
DISTRICT II SUPERVISOR

APPROVED BY [Signature] TITLE [Blank] DATE MAY 10 2002

Conditions of approval, if any: