Submit 3 Copies State of New Mexico Form C-103 to Appropriate Minerals and Natural Resources Department Revised 1-1-89 District Office **DISTRICT I** CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 WELL API NO. 2040 Pacheco St. 30-015-32121 N Santa Fe. NM 87505 DISTRICT II P.O. Drawer DD, Artesia, NM aspno ART sIndicate Type of Lease STATE X FEE **DISTRICT III** State Oil & Gas Lease No. 1000 Rio Brazos Rd., Axtec NM 87410 L-4500 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" Stetson Creek 13 State Com (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: OIL WELL 2Name of Operator «Well No. Mewbourne Oil Company 1 3Address of Operator Pool name or Wildcat PO Box 5270, Hobbs, New Mexico Baldridge Canyon Morrow ₄Well Location 700 North Unit Letter Feet From The 1900 West Feet From The Section 13 **24S** 24E Range **NMPM** Eddy County 10 Elevation (Show whether DF, RKB, RT, GR, etc.) 4158' GL 11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PLUG AND ABANDON PERFORM REMEDIAL WORK REMEDIAL WORK ALTERING CASING **TEMPORARILY ABANDON** CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ANBANDONMEN PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: 2Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 01/19/02...MI & spud 17 1/2" hole. TD'ed 17 1/2" hole @ 430'. Ran 430' 13 3/8" 48# H-40 ST/C csg. Cemented w/ 250 sks BJ Lite w/ additives. Mixed @ 12.5#/g & 1.98 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8#/g & 1.34 yd,. Circl 70 sks to pit. WOC 18 hrs. Tested BOP to 1000 psi. OK. Drilled out w/ 12 1/4" bit. 01/26/02...TD'ed 12 1/4" hole @ 2715' w/ air. Ran 2715' 8 5/8" 32# J-55 ST/C csg. Cemented w/ 250 sks Thixotropic 'H' w/ additives Mixed @ 14.6#/g & 1.52 yd. Followed w/ 1000 sks BJ Lite w/ additives. Mixed @ 12.5#/g & 1.98 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8#/g & 1.34 yd,. Circl 112 sks to pit. WOC 18 hrs. Tested BOP to 2500 psi. OK. Drilled out w/ 7 7/8" bit. I hereby certify that the information above is true and complete to the best of my knowledge and belief. SIGNATURE TITLE District Manager DATE 02-06-02

> ORIGINAL SIGNED BY TIM DISTRICT II SUPERVISOR

TELEPHONE NO. 505-393-5905

CONDITIONS OF APPROVAL, IF ANY:

(This space for State Use)

APPROVED BY

TYPE OR PRINT NAME N.M. YOUNG