

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87400

OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

RECEIVED  
OCD - ARTESIA

WELL API NO. 30-015-32220
Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
State Oil & Gas Lease No. LG-5172
Lease Name or Unit Agreement Name Outlaw Flats 1 State
Well No. 1
Pool name or Wildcat Baldridge Canyon Morrow

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
Name of Operator Mewbourne Oil Company	
Address of Operator PO Box 5270, Hobbs, New Mexico 88241	
Well Location Unit Letter O : 660 Feet From The South Line and 1400 Feet From The East Line Section 1 Township 24S Range 24E NMPM Eddy County	
Elevation (Show whether DF, RKB, RT, GR, etc.) 3958' GL	

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ANBANDONMENT ☐  
CASING TEST AND CEMENT JOB ☒  
OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

03/22/02...Set 37' of 20" csg. Ready mixed to surface.

03/26/02...MI & spud 17 1/2" hole.

03/27/02...TD'ed 17 1/2" hole @ 404'. Ran 404' 13 3/8" 48 #/ft H-40 ST/C csg. Cemented w/ 250 sks BJ Lite w/ additives. Mixed @ 12.5 #/g w/ 1.98 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circl 50 sks to pit. WOC 18 hrs. Test BOP & equipment to 500 psi. OK. Drilled out w/ 12 1/4" bit.

04/02/02...TD'ed 12 1/4" hole @ 2725'. Ran 2725' 8 5/8" 32 #/ft J-55 ST/C csg. Cemented w/ 860 sks BJ Lite w/ additives. Mixed @ 12.5 #/g w/ 1.98 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g w/ 1.34 yd. Circl 85 sks to pit. WOC 18 hrs. Test BOP & equipment to 2500 psi. OK. Drilled out w/ 7 7/8" bit.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE District Manager DATE 04-16-02

TYPE OR PRINT NAME N.M. Young TELEPHONE NO 505-393-5905

(This space for State Use)

APPROVED BY

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 24 2002