

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

## OIL CONSERVATION DIVISION

2040 Pacheco St.  
Santa Fe, NM 87505

WELL API NO.  
30-015-32409

Indicate Type of Lease  
STATE ☐ FEE ☒

State Oil & Gas Lease No.

Lease Name or Unit Agreement Name  
Layla 35 Fee Com

Well No.  
1

Pool name or Wildcat  
S. Culebra Bluff Atoka

Unit Letter I 1650 Feet From The South Line and 1241 Feet From The East Line

Section 35 Township 23S Range 28E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)  
3002' GL

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

Type of Well:

OIL WELL ☐

GAS WELL ☒

OTHER

Name of Operator  
Mewbourne Oil Company 14744

Address of Operator  
PO Box 5270, Hobbs, NM 88241

Well Location

Unit Letter I 1650 Feet From The South Line and 1241 Feet From The East Line

Section 35 Township 23S Range 28E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)  
3002' GL

11

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

### SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ANBANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-15-02...Spud 17 1/2" hole. TD'ed @ 510'. Ran 510' of 13 3/8" 48# H-40 ST/C csg. Cemented w/ 250 sks 65/35/6 'C' Poz w/ additives. Mixed @ 12.5 #/g & 1.97 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 83 sks to pit. WOC 18 hrs. Test BOP to 1500 psi. OK. Drill out w/ 12 1/4" bit.

12-26-02...TD'ed 12 1/4" hole @ 4315'. Ran 4258' of 9 5/8" 40# J & N-80 LT/C csg. Cemented w/ 1600 sks 65/35/6 'C' Poz w/ additives. Mixed @ 12.5 #/g & 2.04 yd. Tailed w/ 200 sks 'C' w/ 2% CaCl2. Mixed @ 14.8 #/g & 1.34 yd. Circl 50 sks to pit. WOC 18 hrs. Test BOP to 2500 psi. OK. Drilled out w/ 8 3/4" bit. Will test BOP equipment with 3rd party on trip before Wolfcamp.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE N.M. Young TITLE District Manager

DATE 12-31-02

TYPE OR PRINT NAME N.M. Young

TELEPHONE NO. 505-393-5905

(This space for State Use)

ORIGINAL SIGNED BY TIM W. GUM  
DISTRICT II SUPERVISOR

JAN 08 2003

APPROVED BY [Signature] TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: