

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

1.). Com 187 Artesia, New Few Co

7eril 25, %

78000-210-05

er. John A. Tates . n. Pox 1267 Artesia, Wew Mexico

Re: 011 and Las Lease

Dear Sire

Your "Subsequent Report of Abandonment" Rated Rebrusry (, 1956, covering your well No. 1-Matlock located in the Markey, section ., T. 26 S., R. 24 E., Wildcat Area, Eddy County, New Mexico, is hereby approved.

Very truly pours,

John A. Frost Fistrict Engineer

JAF : 1982

Inspected by John to Front April 13, 1956

the fish

The state of the s

UNUTED ETATES • DEPART VESTION, THE HERMON • LUCKOSIGNE NO.



Fort (F	n 9-3 eb. 19	331 a 51)	
ſ			
		-	 -

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Las Cruces
Lease No	067155
Unit	В

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) Artesia, New Mexico. February 3,	NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY
The elevation of the derrick floor above sea level is ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen ing points, and all other important proposed work) Pulled 1375' of 3 5/8" casing. Filled hole with stud and ran 15 sacks of cement at Total Depth. 15 Sacks of Cement at 2600 feet and 20 sacks of cement at 800 feet. Knocked off 10 3/4 casing at 600 feet. Shot 13" casing at 400 feet, bridged hole and ran 10 sacks of cement at 4000 feet. Filled hole with heavy mud and set regulation marker in 10 sacks of pement. Finished plugging and abandoming on January 27, 1956. Cleaned up location in the company of the communication of the		February 8, 19.56
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen ing points, and all other important proposed work) Pulled 1375' of 3 5/8" casing. Filled hole with mud and ran 15 sacks of cament at Total Depth. 15 Sacks of Cament at 2600 feet and 20 sacks of cament at 800 feet. Knocked off 10 3/4" casing at 600 feet. Shot 13" casing at 400 feet, bridged hole and ran 10 sacks of cament at 4006 feet. Filled hole with heavy mud and set regulation marker in 10 sacks of pament. Finished plugging and abandoning on January 27, 1956. Cleaned up location [understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Company John A. Yates	NE 1 Sec. and Sec. No.) Wildcas (Field)	(Range) (Brendian)
Pulled 1375' of \$ 5/8" casing. Filled hole with mud and ran 15 sacks of cement at 2600 feet and 20 sacks of cement at 800 feet. Knocked off 10 3/4" casing at 600 feet. Shot 13" casing at 400 feet, bridged hole and ran 10 sacks of cement at 4000 feet. Filled hole with heavy mud and set regulation marker in 10 sacks of pement. Finished plugging and abandoning on January 27, 1956. Cleaned up location to the same of the same o	he elevation of the derrick floor above sea ic	vel 18 It.
Company	DETAI	us of work
	Pulled 1375' of \$5/8" casing 15 sacks of casent at Total I feet and 20 sacks of casent at and 138 and ran 10 sacks of casent at and ran 10 sacks of casent at an and ran 10 sacks of casent at an an analysis and ran 10 sacks of casent at an analysis and ran 10 sacks of casent at an analysis and ran 10 sacks of casent at an	ILS OF WORK zes, weights, and lengths of proposed easings; indicate mudding jobs, cemen other important proposed work) Filled hole with mud and ran Depth. 15 Sacks of Coment at 2600 at 800 feet. Knocked off 10 3/4; casing at 400 feet, bridged hole to 400 feet. Filled hole with heavy
	Pulled 1375' of 3 5/8" casing 15 sacks of cament at Total I feet and 20 sacks of cament at Total I casing at 600 feet. Shot 13' and ran 10 sacks of cament at mud and set regulation market plugging and abandoning on James I understand that this plan of work must receive approval	ILS OF WORK zes, weights, and lengths of proposed casings; indicate mudding jobs, cemen other important proposed work) Filled hole with saud and ran Depth. 15 Sacks of Coment at 2600 at 800 feet. Knocked off 10 3/4: casing at 400 feet, bridged hole t 4006 feet. Filled hole with heavy r in 10 sacks of pement. Finished anuary 27, 1956. Cleaned up location.

16" \$437" à