(Feb. 1951)	Approval expires 12-31-60.
	SUBMIT IN TRIPLICATE) Land Office 0.506 -A
D B FORTH CONTRACTOR	
APPROVER.	TMENT OF THE INTERIOR
DETAR	UNITED STATES TMENT OF THE INTERIOR GEOLOGICAL SURVEY
8 1962	GEOLOGICAL SURVEY JUN 2 2 1962
Tout Tout	JUN 2 2 1000
DISTRICT ENGINEER	NOON THE PROPERTY OF THE PROPE
SUNDRY NOTICE	ES AND REPORTS ON WELLS, C. C.
	ES AND REPORTS ON WELLS, C. C.
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	1 1
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE	
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CH	ECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	Time 1944
HILL & MEEKER - Carper-Fe	June 12th, 19 62
Well No. One is located 650	ft. from $\begin{bmatrix} \mathbf{N} \\ \mathbf{S}^{\mathbf{z}} \end{bmatrix}$ line and $\begin{bmatrix} 660 \\ \mathbf{S}^{\mathbf{z}} \end{bmatrix}$ line of sec. $\begin{bmatrix} \mathbf{L} \\ \mathbf{N} \end{bmatrix}$
N4NSA 21 24 S	31-E NMPM
(1/4 Sec. and Sec. No.) (Twp.)	
Wildcat	
Wildcat (Field)	(County or Subdivision) (State or Territory)
	(County or Subdivision) (State or Territory) furnish later.
The elevation of the derrick floor above	(County or Subdivision) (State or Territory) furnish later. e sea level is ft.
The elevation of the derrick floor above	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK
(State names of and expected depths to objective sands ing points	(County or Subdivision) (State or Territory) Furnish Later. sea level is ft. DETAILS OF WORK specification of the proposed casings; indicate mudding jobs, comentation, and all other important proposed work)
(State names of and expected depths to objective sands ing points This well will be drilled with r then cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK
(State names of and expected depths to objective sands ing points This well will be drilled with r then cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK state show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentant and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and Se will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth
(State names of and expected depths to objective sands ing points This well will be drilled with r then cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/	(County or Subdivision) furnish later. sea level isft. DETAILS OF WORK state show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentate and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and Sea will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth berforated and treated, if necessary.
(State names of and expected depths to objective sands ing points This well will be drilled with r then cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentant and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and We will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth berforated and treated, if necessary. RECENCED JUN 181962
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled with rethen cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/and pay section will be p	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment, and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and We will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth perforated and treated, if necessary. RECENCED JUN 181962 U. S. GEGLOGICAL SURVEY
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled with rethen cored to total depth of 8 5/8" 24# surface case production is found, 4 1/8 and pay section will be p	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentant and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and We will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth berforated and treated, if necessary. RECENCED JUN 181962
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled with rethen cored to total depth of 8 5/8" 24# surface cas production is found, 4 1/and pay section will be p	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment, and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and We will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth perforated and treated, if necessary. RECENCED JUN 181962 U. S. GEGLOGICAL SURVEY
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled with return cored to total depth of 8 5/8" 24% surface case production is found, 4 1/2 and pay section will be possible that this plan of work must receive as HILL & PEEKER Company	(County or Subdivision) furnish later. sea level isft. DETAILS OF WORK is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentation and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and is we will run approximately 350 feet using, circulate cement to surface. If /2" casing will be cemented at total depth perforated and treated, if necessary. FECTIVED JUN 181962 U. S. GEOLOGICAL SURVEY perovaled to the commenced.
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled It will be drilled with rethen cored to total depth of 8 5/8" 24# surface case production is found, 4 1/2 and pay section will be purposed to the production of the found of the pay section will be purposed to the pay section will be pay section will be purposed to the pay section will be pay secti	(County or Subdivision) furnish later. sea level isft. DETAILS OF WORK is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comentation and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and is we will run approximately 350 feet using, circulate cement to surface. If /2" casing will be cemented at total depth perforated and treated, if necessary. FECTIVED JUN 181962 U. S. GEOLOGICAL SURVEY perovaled to the commenced.
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled with return cored to total depth of 8 5/8" 24% surface case production is found, 4 1/2 and pay section will be possible that this plan of work must receive as HILL & PEEKER Company	(County or Subdivision) furnish later. sea level is ft. DETAILS OF WORK is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coment, and all other important proposed work) I to an approximate depth of 4300 feet. rotary to top of the Delaware Sand and i. We will run approximately 350 feet ling, circulate cement to surface. If 2" casing will be cemented at total depth perforated and treated, if necessary. RECCENCED JUN 181962 U. S. GEOLOGICAL SURVEY percovally results. Bldg.,
(State names of and expected depths to objective sands ing points This well will be drilled It will be drilled It will be drilled with rethen cored to total depth of 8 5/8" 24# surface case production is found, 4 1/2 and pay section will be purposed to the production of the found of the pay section will be purposed to the pay section will be pay section will be purposed to the pay section will be pay secti	County or Subdivision) Furnish later. sea level isft. DETAILS OF WORK is show sizes, weights, and lengths of proposed casings; indicate mudding jobs, coments, and all other important proposed work) I to an approximate depth of 4300 feet. Totary to top of the Delaware Sand and i. We will run approximately 350 feet sing, circulate cement to surface. If 2" casing will be cemented at total depth berforated and treated, if necessary. FINALLY MENTALLY PROPERTY OF THE PROPERTY O

NUMBER OF COPIES RECEIVED						
DISTRIBUTION						
ITA FE						
FILE						
U,5.G.5						
LAND OFFICE						
TRANSPORTER	OIL					
	G A 3					
PRORATION OFFI	E	7				

DISTRIBUTION		NEW MEX	CO OIL CONS	ERVATION	COMMISSION	FORM C=128 Revised 5/1/57			
J.5.G.5		WELL LOCATION AND ACREAGE DEDICATION PLAY							
TRANSPORTER GAS	s	SEE INSTRUCTIONS FOR COMPLETING THIS FORM ON THE REVERSE SIDE							
PRORATION OFFICE									
			SECTION A			rang banasa in George George (1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 1914 - 191			
Operator			Lease			Well No.			
Hill & Me				r-Federal	21	One			
Unit Letter Sect	21 To	waship 24 S	Range 31 E	County E.C	ddy County	N.M.			
Actual Footage Location 660 fee	on of Well: t from the Nort	h line and	660	feet from the	Z-st	line			
found cal Elev.	Producing Forma De Lawa	rion re Sand	Pool Wilde	at	Ded	licated Acreage: 40 Acres			
who has the right to another. (65-3-29	drill into and to p (e) NMSA 1935 C stion one is "no," NO If ans	oroduce from any poo omp.) 'have the interests wer is ''yes,'' Type	of all the owners l of Consolidation and their respecti	e the production	either for himself	'Owner' means the person or for himself and ion agreement or other-			
	ty apple to the control of the contr	SECTION B			CEI	RTIFICATION			
				`0 0' 660'	in SECTION A	Meeker			
					Date I hereby certif	y that the well location plat in SECTION B was			
					plotted from fi surveys made supervision, a and correct to and belief. Date Surveyed	eld notes of actual by me or under my nd that the same is true the best of my knowledge			
0 330 660 990	1320 1650 1980		00 1500 100	0 500		ofessional Engineer urvey or			

INSTRUCTIONS FOR COMPLETION OF FORM C-128

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plan the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of the Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3 of Section A, please use space below.