

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0472258 (A)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government M

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Washington Ranch Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 27-T25S-R24E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

CITIES SERVICE OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. Box 69, Hobbs, New Mexico 38240

4. LOCATION OF WELL (Report location clearly and in accordance with any State Requirements. See also space 17 below)

At surface

660' FSL & 1980' FWL of Sec 27-T25S-R24E, Eddy County, N.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3715 GF Est.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Cement surface pipe

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 750' No returns. Prep to drill ahead. Ran 24 joints (762.47) 8 5/8" OD 24# K-55 casing set and cemented @ 749 W/200 sacks Halliburton Light W/2% CaCl₂ + 10# Gilsenite + 1/4# Flocele/sack + 150 sacks Class "C" W/2% CaCl₂. Cement did not circulate. Plug down @ 12:10 P.M. on 4-2-72. WOC 4 hrs. Cemented annulus from surface W/7 1/2 yards remix. WOC 4 hrs. Cement fell back 16' from surface. Filled annulus outside of 8 5/8" surface with Redmix concrete. WOC 20 hrs. Total WOC time 28 hrs. Tested 8 5/8" casing and rams W/1000 psi for 30 minutes with no drop in pressure.

RECEIVED

APR 28 1972

U.S. GEOLOGICAL SURVEY

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Admin. Supervisor

DATE 4-24-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection, looking to approval of the abandonment.