

NMOCC COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUBMIT IN TRIP
(Other instruction
verse side)
DATE
re-Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM-17225-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Ross Draw

8. FARM OR LEASE NAME

Ross Draw Unit

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-26S-30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

2971.1' GR

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

1.

OIL ☐ GAS ☒ OTHER

2. NAME OF OPERATOR

Penroc Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Drawer 831, Midland, Tx. 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1980' FSL, 660' FEL

RECEIVED

JUN 24 1977

O. C. C.

ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) Re-enter and Deepen

☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6/20/77

Well was drilled to total depth 7265' and plugged although final plugging report was never submitted. Temporary abandonment.

Plan to re-enter, drill cement plug in top of 9 5/8" casing, drill plug at 1550-1650', and run 7" casing (26# N-80) to approximately 3350 feet and cement with approximately 350 sxs.

Then drill remaining cement plugs @ 3350-3400', 4900-5000', and 6500-6650'. Deepen well to approximately 8900' to test the Bone Spring formation.

RECEIVED

JUN 22 1977

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

B. J. Dacey

TITLE President

DATE 6/21/77

(This space for Federal or State office use)

APPROVED BY

Joe A. Lara

TITLE ACTING DISTRICT ENGINEER

DATE JUN 23 1977

CONDITIONS OF APPROVAL, IF ANY: