

~~CONFIDENTIAL~~ OFFICE COPY

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other ☐ Dry Hole

2. NAME OF OPERATOR
Penroc Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Drawer 831, Midland, Tx. 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980'FSL, 660'FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
NM-17225-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
Ross Draw

8. FARM OR LEASE NAME
Ross Draw Unit

9. WELL NO.
6

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
28-26S-30E

12. COUNTY OR PARISH
Eddy

13. STATE
N. M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
2971.1' GR

RECEIVED

NOV 10 1980

O. C. D.
ARTESIA, OFFICE

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☒
☐
☐
☒

RECEIVED

FEB 1 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

**U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO**

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/5/77: Total depth 8837'
1. set 150' cement plug 7350-7200'
2. set 150' cement plug 5900-5750'
3. set 150' cement plug 4400-4250'
4. set 100' cement plug 3400-3300'

7/11/77: Rig up casing pulling unit, shoot 7", 26#, N-80 LT&C casing off @ 3063'. Recovered 97 jts, being 3063'.

7/13/77: 1. set 100' cement plug 1650-1550'
2. set 20' cement plug in top 9 5/8" surface casing.
Install dry-hole marker. Well P&A.

12/4/77: Fill & level pits, rip pad and access road.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED B. J. Dally TITLE President DATE January 31, 1980

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: