

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ JUL 2 1981

2. NAME OF OPERATOR  
Pogo Producing Company / O. C. D.

3. ADDRESS OF OPERATOR ARTEZIA, OFFICE  
P.O. Box 10340 Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 580' FNL & 2130' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input checked="" type="checkbox"/>
(other)			

5. LEASE  
NM 12559

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Brantley Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 23, T-26-S, R-28-E

12. COUNTY OR PARISH  
Eddy

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
2954' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

12/11/80: 2640' MW 10.4, Vis 36. Logged w/Schlumberger - HOWCO spotted Plug #1 @ 2540'-2640' w/75 sxs Cl C cement w/0.5% HR-4. Plug #2 @ 1430'-1530' w/50 sxs Cl C cement w/0.5% HR-4.

12/12/80: HOWCO spotted cem Plug #3 @ 170'-270' w/50 sxs Cl C Neat. Plug #4 from surface to 10' w/10 sxs Cl C Neat.

12/13/80: Cut off well head, weld on plate and marker, clean up location, fence mud pits. P & A 12/12/80 as dry hole. FINAL REPORT.

Casing left in hole: 219.08' 10 3/4" 40.5# K-55 Rge 3 STC @ 220'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED P. Williams TITLE Div. Oper. Mgr. DATE December 22, 1980

APPROVED (This space for Federal or State office use)

(Orig. Sgd.) PETER W. CHESTER TITLE \_\_\_\_\_ DATE \_\_\_\_\_

APPROVED BY \_\_\_\_\_ CONDITIONS OF APPROVAL, IF ANY, \_\_\_\_\_

JUN 30 1981

FOR  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

See Instructions on Reverse Side