MS OTL Copy , for a 100 00 December 1.

UNITED STATES Artesia, 1 8387 5 15

Form Approved. Budget Bureau No. 42-R1424

·			
5. Lf	ASE 06158	1	RECEIVED

_			
i.	IF INDIAN, ALLOTTEE OR TRIBE NAME FEB	24	1982

DEPARTMENT OF THE INTERIOR	LC 061581
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME FEB 24 1982
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME O. C. D.
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME ARTESIA, OFFICE
1. oil gas de other	Brushy Draw Deep Federal 9. WELL NO.
2. NAME OF OPERATOR	
Fuller Petroleum, Inc./	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Ft. Worth	Wildcat 7/10 1550
2020 Ft.Worth Nat'l Bank Bldg., Texas 76102	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA ***********************************
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Sec 24, T-26-S, R-29-E
below.) AT SURFACE: 990' FNL & 1980' FWL, 24-26S-29E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	Eddy New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 2977' G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Casing and cementing 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state)	S L SURVEY MEXICO e all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertiner	lirectionally drilled, give subsurface locations and nt to this work.)*
Spudded well at 7:00 P.M., January 10, 1982.	Drilled to 376' KB.
Ran ll joints, 369', 20", 94#/ft., K-55 & H-4 Set casing at 367' KB.	40 Buttress casing.
Halliburton cemented with 800 sx Class "C" w Plug down at 9:30 P.M., January 12, 1982. Circulated 65 sx cement to surface.	ith 2% CaCl2.
WOC 50 hours. Tested casing to 1500 psi for pressure loss.	30 minutes with no
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED TITLE Agent	DATEJanuary 25, 1982

ROGER A. CHAPMAN (This space (This space for Federal or State office use) APPROVED BY CONDITIONS PE BPROJALIORANY: _____ TITLE ______ DATE ___

U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

*See Instructions on Reverse Side