UNITED SINE ELIVED BY	5. LF4SE
DEPARTME OF THE INTERIOR	NM-22207 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
GEOLOGICAL SUPPLEY3 1984	6. IF INDIAN, ALLOTTEE ON THIS ETTING
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to crill or to ARTESIA; Dig back to a different reservoir. Use Form 9-331-C for such proposals)	8. FARM OR LEASE NAME
	Washington Ranch Storage Project
1. oil Ras Well Other Gas Storage 2. NAME OF OPERATOR	9. WELL NO. 21
El Paso Natural Gas Co.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Washington Ranch Morrow
1800 Wilco Bldg., Midland, Tx 79701	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below)	Sec. 34, T-25-S, R-24-E
AT SURFACE: 2150' FSL & 2150' FWL AT TOP PROD. INTERVAL:	Eddy N. Mex
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AT 110.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	GR 3718'
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT L.	
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING []	change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES L L L L L L L L L L L L L L L L L L L	
(other)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dismeasured and true vertical depths for all markers and zones pertinent	rectionally drilled, give subsurface locations and
1.) Set tubing plug. RU and install 50	00 psi hydraulic BOP.
2) Pig up Spubbing unit, pull and lay down 2 7/8" production tubing.	
3.) RU wireline unit and set Baker Model FA-1 permanent packer at 6600'	
wlm, with blanking plug below packer.	
4.) Load 7" casing with water and pressure test to 3000 psig.	
5.) Run 4½" 11.6# K-55 tubing with Baker K-22 latch in seal assembly,	
riculate inhibited packer fluid, latch into packer.	
7.) Pressure test tubing to 3000 psig.	Retrieve Blanking Plug.
7.) Pressure test tubing to 3000 psig. return to service.	Retrieve blanking 1266,
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	-
ACCEPTED FOR RECORDING space for Federal or State office	DATE 9-10-84
CCEPTED FOR RECORDING source for Federal or State office	e use)
APPROVED BY	
CONDITIONS OF APPROVAL IF ANY:	DATE
SEP 1 2 1984	

() aclastrate, NEW MEXICO *See Instructions on Reverse Side