

RECEIVED

OCT 8 1982

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
ARTESIA, OFFICE

OIL CONS. COMMISSION  
Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
Amoco Production Company ✓  
3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, New Mexico 88240  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FSL X 1980' FEL, Sec. 22  
AT TOP PROD. INTERVAL: (Unit J, NW/4, SE/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:  
TEST WATER SHUT-OFF ☐ ☐  
FRACTURE TREAT ☐ ☐  
SHOOT OR ACIDIZE ☐ ☐  
REPAIR WELL ☐ ☐  
PULL OR ALTER CASING ☐ ☐  
MULTIPLE COMPLETE ☐ ☐  
CHANGE ZONES ☐ ☐  
ABANDON\* ☐ ☐  
(other) Run casing

5. LEASE  
NM-16131  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Federal "DB"  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Und. Morrow  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
22-25-31  
12. COUNTY OR PARISH  
Eddy  
13. STATE  
NM  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3348' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to TD of 4248'. Ran 10-3/4" S-95 65.7 lb/ft. casing set at 4248'. Cemented with 5200 sacks class C lite with .3% Halad 4 and 200 sacks class C with .3% Halad 4. Circulated 1100 sacks. WOC 18 hours. Drilled out cement to 4207'. Tested casing to 1500 PSI for 15 minutes. Tested O.K. Reduced bit to 9-1/2" and resumed drilling. Drilled to TD of 12120'. Ran 7-5/8" P-110 and S-95 39 lb/ft casing set at 12120'. Cemented with 1300 sacks class H lite and 500 sacks class H. Reduced bit to 6-1/2" and resumed drilling. Currently drilling.

0+6-MMS, R 1-HOU 1-W. Stafford, HOU 1-DMF

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Turner TITLE Ast. Adm. Analyst DATE 9-29-82

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD  
OCT 6 1982  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

(This space for Federal or State office use)

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

Instructions on Reverse Side