

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
2040 South Pacheco  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

<b>SUNDRY NOTICES AND REPORTS ON WELLS</b> (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-30888
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator ENERGEN RESOURCES CORPORATION		6. State Oil & Gas Lease No.
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401		7. Lease Name or Unit Agreement Name: Culpepper Martin
4. Well Location Unit Letter <u>L</u> : <u>1790</u> feet from the <u>South</u> line and <u>660</u> feet from the <u>West</u> line Section <u>6</u> Township <u>31N</u> Range <u>12W</u> NMPM County <u>San Juan</u>		8. Well No. 4B
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5831 GR		9. Pool name or Wildcat Blanco Mesaverde

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐

OTHER: Add Menefee Pay

☒ OTHER:

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

It is intended to add the Menefee to the existing Mesa Verde as follows:

1. MIRU. TOH with tubing.
2. Set RBP at 4500'. Test casing to 3000 psi.
3. Selectively perforate Menefee from 4130-4480'. Fracture treat with 60Q foam
4. Flow back well. TIH to RBP and retrieve. TOH. TIH and clean out to PBTD.
5. Land tubing at 4740'. Nipple up wellhead and return to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 1/8/03

Type or print name Vicki Donaghey Telephone No. 505-325-6800

(This space for State use)

APPROVED BY [Signature] TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 43 DATE JAN 10 2003

Conditions of approval, if any: