UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial N

6. If Indian, Allotee or Tribe Name

SF 079366

SUNDRY NOTICES AND REPORTS ON WELLS	>

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT"-for such proposals

Dispose Water

	7, If Unit or CA. Agreement Designation
SUBMIT IN TRIPLICATE	7. If Orlit of CA. Agreement Designation
T. Superfilled	RINCON UNIT
1. Type of Well	8. Well Name and No.
Oil X Well Other	
2. Name of Operator	RINCON UNIT No 174R
	9. API Well No.
PURE RESOURCES	30-039-27008
3. Address and Telephone No.	10. Field and Pool, or Exploration Area
P.O. BOX 850 - BLOOMFIELD, NM 87413	
4. Location of Well (Footage, Sec., T., R., or Survey Description)	Basin Dakota
1041' FNL & 785' FWL	11. County or Parish, State
"D" SEC. 19 T27N-R06W	RIO ARRIBA, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent Abandonment	Change of Plans
Recompletion	New Construction
	Non-routine Fracturing
	Water Shut-Off
Casing Repair	
Final Abandonment Notice Altering Casing	Conversion to Injection

13. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)*

SEE ATTACHED

COMPLETION SUNDRY



RECEIVED

70 JAN 30 AM II: 15

Signed Mike Phillips	Title SAN JUAN BASIN DRILLING/PRODUCTION FOREMAN	ACCEPTED 11/24/03
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	DatE E B 0 4 2003

Title 18 U.S.C. Sections 1001, makes is a crime for any person knowingly and willfully to make to any department or agency of the united states of false, fictitious of fraudulent st of representations as to any matter within its jurisdictions.

Pure Resources, Inc. Well History

Lease Weil 521523-174R Well Name RINCON UNIT #174R - 76.82% WI County: RIO ARRIBA State: NM MIRU COBRA WL. RAN DEVIATION SURVEY TO 7536'. 12/16/2002 MIRU SERVICE UNIT TO CLEAN OUT TO PBTD. SD DUE TO BAD WEATHER. 12/17/2002 TIH W/ 3-7/8" BIT. CLEAN OUT TO 7596'. CIRC HOLE CLEAN. P-TEST TO 1000# - HELD OK. TOH W/ TBG & BIT. RD TO 12/18/2002 MOVE. MIRU SCHLUMBERGER, RUN CCL, GR, TDT LOG. 12/26/2002 RU SCHLUMBERGER WL & PERF AS FOLLOWS: 7594, 7592, 7582, 7569, 7567, 7555, 7546, 7541, 7526, 7516, 7508, 7491, 1/15/2003 7482, 7474, 7450, 7435, 7433, 7431, 7424, 7418, 7404, 7393, 7388, 7382'. ALL SHOTS .38, 1 SPF. FLOW WELL TO BLOW PIT ON 1/8" CHOKE W/ 2850# ON WELL TO 600# ON 3/8" CHOKE - GOOD FLARE TO BLOW PIT. 1/17/2003 AFTER 20 HRS OF BLOWING WELL, SWI FOR PRESSURE SURVEY MONDAY MORNING. RECOVERED APPROX 300 BBLS FLUID. MIRU COBRA WL. RUN PRESSURE SURVEY ON DAKOTA FORMATION. 1/20/2003 FIRST DELIVER WELL TO METER #98670, 1120# ON CSG. MAKING 1.4 MCFPD W/ FLOWBACK CREW ON LOCATION 1/21/2003

1/21/03 @ 2:00 P.M.

1/22/2003

FLOWED 602 MCFD + 0 BO + 0 BW IN 20 HRS.

CASING HISTORY REPORT

SURFACE LEVEL

Location NW SEC	17, T27N, R6W			
TD Date 12/2/2002	2 TD Hole	Total Depth: 388	Ho	ole 12-1/4"
Joints	Joint Description		Total	Running
	SAWTOOTH COLLAR		1.00	1.00
1	9-5/8" 32.3# STC CSG		40.97	41.97
	INSERT FLOAT		0.00	41.97
8	9-5/8" 32.3# STC CSG		325.43	367.40
	WELLHEAD	* * * *	1.50	368.90
	KB		15.00	383.90
9	Total Joints Ran		383.90	

Cemented as Top Cement:

Stage 1 - 225 SX TYPE 111 W/ 2% CACL2, .25% CELLOFLAKE MIXED @ 6.7 GAL/SK (YLD:1.39, WT:14.60)

1st INTERMEDIATE LEVEL

Location NW SEC	17, T27N, R6W		ing the second of the second o	
TD Date 12/4/2002		Total Depth: 2705		ole 8-3/4"
Joints	Joint Description		Total	Running
64	7" 20# K-55 STC CSG		2639.11	2639.11
	FLOAT COLLAR		1.00	2640.11
	SAWTOOTH COLLAR		1.00	2641.11
	MANDREL		1.50	2642.61
1	7" 20# K-55 STC CSG		41.22	2683.83
	FLOAT COLLAR		1.00	2684.83
	KB		15.00	2699.83
65	Total Joints Ran		2699.83	

Cemented as

Top Cement:

Stage 1 - 325 SX TYPE "F" W/ 2% CACL2, .25% CELLOFLAKE, 8% GEL, 6.25 PPS LCM-1 MIXED @ 11.9 GAL/AK (YLD:2.11, WT:12.10) Tail: 80 SX TYPE 111 W/ 2% CACL2, .25% CACL2, .25% CELLOFLAKE MIXED @ 6.7 GAL/SK (YLD:1.39, WT:14.60)

2nd INTERMEDIATE LEVEL

Location NW SEC	17, T27N, R6W			
TD Date 12/7/2003	2 TD Hole	Total Depth: 7605	Н	ole 6-1/4"
Joints	Joint Description		Total	Running
	FLOAT SHOE		1.00	, 1.00
	FLOAT COLLAR		1.00	2.00
	KB		15.00	17.00
4	4-1/2" 11.60# I-80 LT&C CSG		168.85	185.85
1	4-1/2" 11.60# N-80 LTC CSG		42.19	228.04
175	4-1/2" 11.60# I-80 LTC CSG		7362.06	7590.10
1	MARKER JT		14.20	7604.30
181	Total Joints Ran		7604.30	

Cemented as Top Cement:

Stage 1 - 85 SX TYPE 111 PREM LITE HIGH STRENGTH W/ 2% CACL2, 5 PPS LCM-1, .25 PPS CF, 1% FL-52, .3% CD-32, .3% R-3 MIXED @ 12.7 GAL/SK (YLD:2.37, WT:11.90)Tail: 525 SX SAME AS LEAD MIXED @ 10.1 GAL/SK (YLD:2.02, WT:12.50)