Form 3160-5 (August 1999)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

**BUREAU OF LAND MANAGEMENT** 

SUNDRY NOTICES AND REPORTS ON WELLS

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMNM10171

abandoned wel	I. Use form 3160-3 (APD) for	r such proposals.	6. If Indian, Allottee	or Tribe Name
SUBMIT IN TRIF	PLICATE - Other instructions	on reverse side.	7. If Unit or CA/Agr	reement, Name and/or No.
1. Type of Well	<del></del>	<u> </u>	8. Well Name and N LA PLATA 20 1	0.
Oil Well Gas Well Oth		10 Land		
2. Name of Operator TEXAKOMA OIL & GAS COR	SPRINKLE U il: tls2@airmail.net	19. API Well No. 30-045-31311-00-X1		
3a. Address 5400 LBJ FRWY, SUITE 500 DALLAS, TX 75240	Ph: Fx:	Phone No (include area code 972.70 1.9106 972.701.9056	BASIN FRUIT	LAND COAL
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)	206,00,00	11. County or Parisl	n, and State
Sec 20 T31N R13W NWNW 6	880FNL 1196FWL		SAN JUAN CO	DUNTY, NM
12. CHECK APPE	ROPRIATE BOX(ES) TO INI	DICATE NATURE OF	NOTICE, REPORT, OR OTH	ER DATA
TYPE OF SUBMISSION	TYPE OF ACTION			
- Notice of Intent	□ Acidize	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off
□ Notice of Intent	Alter Casing	☐ Fracture Treat	☐ Reclamation	□ Well Integrity
Subsequent Report	☐ Casing Repair	■ New Construction	Recomplete	Other
Final Abandonment Notice	☐ Change Plans	☐ Plug and Abandon	Temporarily Abandon	Brilling Operations
	Convert to Injection	□ Plug Back	☐ Water Disposal	
determined that the site is ready for form of the surface casing was run a 1/4#/sack Flocele mixed at 15 surface. Installed casing hear casing, tested casing and BO Schlumberger ran open hole casing to 1784' with insert flow preflush water and 75 Sks Clamixed at 12.2 ppg, yield 2.25 cf/Sk w/5%Gilsonite/Sk w/2% good cement to reserve pit, retension, installed tubing head	4-03. An 8 3/4" hole was drille and cemented to surface with 6.6 ppg with a yield of 1.18 cf/s d and Annular BOP. Drill ahea P to 1000 psig, 15", held ok. logs on 3-9-03 with LTD 1790' at at 1750'. Halliburton cement as B cement with 2% Econoli cf/Sk and tailed in w/110 Sks CaCl2 w/1/4#/Sk Flocele, dispeleased pressure on float, held	65 Sacks of Class B cersk and 4 bbls of good celd with 6 1/4" bit, tag cer Drilled ahead to DTD 17 KB. Ran 44 Jts of New ted casing to surface wite w/5% Gilsonite/Sk w/5td Cls B mixed at 15.4 blaced with 28 Bbls wated ok. Set casing slips with 28 bbls with 28 bbls wated ok. Set casing slips with 28 bbls wated of the casing slips with 28 bbls wated wated with 28 bbls wated wated wated wated wated w	nent w/2% CaCl2 & ment to nent at 148' in 81'on 3-8-03. 4 1/2" 10.5 ppf J-55 h 10 Bbl 1/4#/Sk Flocele, ppg, yield 1.23 r, circulated 6 Bbls th pipe in full	
14. Thereby certify that the foregoing is	s true and correct. Electronic Submission #1936 For TEXAKOMA OIL & GA ommitted to AFMSS for process	AS CORPORATION, sent	to the Farmington	
Name (Printed/Typed) TOM SPRINKLE		Title DRILL	ING/COMPLETION MANAGER	₹
Signature (Electronic	Submission)	Date 03/10/	2003	
	THIS SPACE FOR F	EDERAL OR STATE	OFFICE USE	
Approved By ACCEPTED			N MASON EUM ENGINEER	Date 03/11/2003
Conditions of approval, if any, are attached certify that the applicant holds legal or eqwhich would entitle the applicant to conditions.	ject lease	Office Farmington		
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	3 U.S.C. Section 1212, make it a crim statements or representations as to an	ne for any person knowingly a ny matter within its jurisdiction	nd willfully to make to any department on.	t or agency of the United