Form 3160-5 (November, 1996)

UNITED STATES DEPARTMENT OF THE INTERIOR A

BUREAU OF LAND MANAGEMEN

FORM APPROVED

OMB No. 1004- 0135 Expires: July 31, 1996

ease Serial No SUNDRY NOTICES AND REPORTS ON W NM-03845 Do not use this form for proposals to drill of to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals ndian, Allottee, or Tribe Name Init or CA. Agreement Designation SUBMIT IN TRIPLICATE- Other Instructions on the reve **Northeast Blanco Unit** 1. Type of Well 8. Well Name and No. X Gas Well Oil Well 2. Name of Operator **NEBU 433A** 9. API Well No. Devon Energy Production Co. L.P. Attn: Kenny Rhoades 3a Address 3b. Phone No. (include area code) 30-045-31440 10. Field and Pool, or Exploratory Area 1751 Highway 511 Navajo Dam, NM 87419 (505)320-6310 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) **Basin Fruitland Coal** 11. County or Parish, State 1345' FNL & 1560' FEL 24 . T 30N R. 8W SW /4. NE Sec. **Unit G** San Juan NM Longitude CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Production (Start/ Resume) Acidize Deepen Water Shut-off Altering Casing Fracture Treat Reclamation Well Integrity Subsequent Report New Construction Other Casing Repair Recomplete **Casing and Cement** Change Plans Plug and abandon Temporarily Abandon Water Disposal Final Abandonment Notice Convert to Injection Plug back 13. Describe Proposed or Completed Operation (clearly state all pertinent details including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths or pertinent markers and sands. Attach the Bond under which the work will performed or provide the Bond No. on file with the BLM/ BIA. Required susequnet reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in anew interval, a Form 3160-4 shall be filed once

determined that the site is ready for final inspection.) Drilled 12-1/4" hole to 302'. On 1/29/2004 set 6 jts 9-5/8" 32.3# casing at 296'. Cemented with 175 sx (37 bbls) "B" cement w/ 2% CaCl2 and 1/4# Flocele. Circulate 17 bbls cement to surface. Test casing to 1500 psi.

testing has been completed. Final Abandonment Notice shall be filed only after all requirements, including reclamantion, have been completed, and the operator has

Drilled 8-3/4" hole to 4109'. On 2/12/2004 set 93 bits 7" 23# casing at 4095'. Cemented w/ 660 sx (172 bbls) 50/50 Poz w/ 3% gel, 0.4% Halad 344, 0.1% CFR-3, 5# Gilsonite, and 1/4# Flocele. Tailed in with 75 sx (13 bbls) class "B" w/ 0.4% Halad 344. Circulate 12 bbls cement to surface. Test casing to 1500 psi.

Drilled 6-1/4" hole to 4434'. Underreamed hole to 9-1/2" from 4095' to 4434'. Utilized natural and air assisted surges to remove near wellbore material. No casing was run or cement pumped in this section of hole. If hole conditions dictate, at a later date we may run a 5-1/2" liner in hole. Production tubing (2-3/8") was set in well at 4313'.

14. I hereby certify that the foregoing is true and correct. Name (Printed/ Typed)	itle	
Kenny Rhoades	Company Representative	
by Klant	3 · 30 - 04	ACCEPTED FOR RECORA
THIS SPACE FOR FED	ERAL OR STATE OFFIC	ŽE ÚŠE
Approved by	Title	APRIME ZUU4
Conditions of approval, if any are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would notife the applicant to conduct approve the second state.		FAHMINGIUM FIELD OFFICE

Title 18 U.S.C. Section1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitio or fraudulent statements or representations as to any matter within its jurisdiction.