

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

2004 MAR 11 AM 11:24

070 Farmington, NM

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT---" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil ☒ Gas ☐ Other

2. Name of Operator

D.J. Simmons Co.

3. Address and Telephone No.

1009 Ridgeway Place, Suite 200, Farmington NM 87401 (505) 326-3753

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface Location: 1623' FNL x 956' FWL, Section 24, T25N, R3W
BHL: 1902' FNL x 2160' FWL, Section 24

5. Lease Designation and Serial No.
NM 105189

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Byrne Federal 24-1X

9. API Well No.

3003927556

10. Field and Pool, or Exploratory Area

West Lindreth Gallup / Blanco MV

11. County or Parish, State

Rio Arriba County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Drilling Operations

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)*

2/01/04: Drilled 12 1/4" hole to 4324', prepare well bore for logs.

2/02/04: Ran Schlumberger Platform Express log suite from 4324' to surface casing. Prepare well bore for casing.

2/03/04: Ran 9 5/8", 36 and 40 ppf, J55 and L80 casing. Landed casing at 4321'. Cemented to surface with 900 sks 65/35 poz followed by 100 sks Class 'G' + 2% CaCl2. Circulated 1 bbl cement to surface.

2/04/04: Cut off 13 3/8" casing head. Weld on 9 5/8" 3000 psi casing head. Pressure tested weld to 600 psi. NU 11", 3000 psi BOPE. Pressure test csg to 1500 psi. Pressure tested BOPE to 3000 psi and 300 psi low.

2/05/04: RU air drilling equipment. Drilled out cement with water. Blew hole dry.

2/06/04: Drilled 8 1/2" hole with air to 5275'.

14. I hereby certify that the foregoing is true and correct

Signed Robert R. Griffie
Robert R. Griffie

Title Operations Manager

(This space for Federal or State office use)

Approved by /s/ David R. Sitzler

Title Division of Multi-Resources

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side