

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other	WELL API NO. 30-045-31276
2. Name of Operator ENERGEN RESOURCES CORPORATION	5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
3. Address of Operator 2198 Bloomfield Highway, Farmington, NM 87401	6. State Oil & Gas Lease No.
4. Well Location Unit Letter <u>J</u> : <u>1745</u> feet from the <u>South</u> line and <u>1620</u> feet from the <u>East</u> line Section <u>06</u> Township <u>31N</u> Range <u>12W</u> NMPM County <u>San Juan</u>	7. Lease Name or Unit Agreement Name: Culpepper Martin
8. Well No. 9S	
9. Pool name or Wildcat Basin Fruitland Coal	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 5918' GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒

OTHER: ☐ OTHER: set casing ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

03/22/03 TD:2369'. PBDT: 2321'. Ran 53 jts. 5-1/2" 15.5# J-55 ST&C casing, set @ 2368'. RU Halliburton. Cement with 310 sks 65/35 Class B poz, 6% gel, 10#/sk gilsonite, 1/2#/sk flocele, 2% CaCl2 followed by 100 sks 50/50 Class B poz, 2% gel, 5#/sk gilsonite, 2% CaCl2, 0.5% Halad-9 (740 cu.ft.). Plug down @ 4:15 pm on 03/23/03. Circulate 70 sks cement to surface. RD Halliburton. ND-BOP. Released rig @ 6:00 am on 03/23/03.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Vicki Donaghey TITLE Production Assistant DATE 03/24/03

Type or print name Vicki Donaghey Telephone No. 505-325-6800

(This space for State use)

APPROVED BY Charlie Herrin TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE MAR 24 2003

Conditions of approval, if any: