

RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

2003 APR -7 PM 12:16

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT---" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil ☒ Gas ☐ Other

2. Name of Operator

D.J. Simmons Co.

3. Address and Telephone No.

1009 Ridgeway Place, Suite 200, Farmington NM 87401

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Surface location: 860' FNL x 1060' FWL, Section 21, T29N, R9W

5. Lease Designation and Serial No.
SF-080245-B

6. If Indian, Allottee or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

10166

8. Well Name and No.

L.V. Hamner A1C

9. API Well No.

30-045-30645

10. Field and Pool, or Exploratory Area

Blanco Mesa Verde

11. County or Parish, State

San Juan County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Spud & Drilling

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depth for all markers and zones pertinent to this work.)*

3/27/03: Spudded L.V. Hamner A1C with Aztec Rig 124 at 9:30 a.m. 3/26/03. Drilled 12 1/4" hole to 277'. Ran 9 5/8", 36 ppf, J55 casing. Landed casing at 277'. Cemented with 245 sks class 'G'. Circulated 5 bbls cement to surface.

3/28/03: NU 9 5/8", 2000 psi BOPE. Pressure tested casing head, blind rams, pipe rams, choke and kill line valves, manifold, kelly valves, and casing to 1500 psi. Drilled 8 3/4" hole to 1948'.

3/29/03: Drilled 8 3/4" hole to 2509'. Ran 7", 20 ppf, J55 casing. Landed casing at 2507'. Cemented with 400 sks 50/50 poz followed by 150 sks class 'G' + 2% CaCl2. Circulated 20 bbls cement to surface.

14. I hereby certify that the foregoing is true and correct

Signed Robert R. Griffie Title Operations Manager

(This space for Federal or State office use)

Approved by _____ Title _____
Conditions of approval, if any:

Date APR 08 2003

FARMINGTON FIELD OFFICE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOC