

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

El Pamco, Inc.

3. Address and Telephone No.

P. O. Box 14738 Albuquerque, NM 87191-4738 (505) 296-5508

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

958' FSL & 820' FEL
Section 25, T29N, R11W

5. Lease Designation and Serial No.

SF 047020 B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ghostrider No. 1

9. API Well No.

30-045-31894

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other Spud well.

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completions or Well Completion or Recompletion Report and Log)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Pressure tested surface casing and BOP to 1000 psi for 15 min. Held OK. Drilled 6 1/4" hole to 1950' KB. Ran 45 jts of 4 1/2", J-55 casing. Casing landed at 1946' KB. Cemented with 140 sx (288 cf) of Class B cement containing 2% sodium metasilicate and 1/4 #/sk cello flakes. Tailed in with 100 sx (118 cf) of Class B cement containing 2% CaCl and 1/4 #/sk cello flakes. Circulated 7 bbls of cement to surface. PBD 1903' KB. Shut in and WOC.


14. I hereby certify that the foregoing is true and correct

Signed Anna S. Delventhal

(This space for Federal or State office)

Approved by

Conditions of approval, if any:



Agent

Date 4/27/2004

ACCEPTED FOR RECORD

APR 30 2004

FARMINGTON FIELD OFFICE

NMOC