| submitted in lieu of Form 3160-5 | | | |
|--|--|---------------------------|----------------------------------|
| UNITED STATES | | | |
| DEPARTMENT OF THE IN | | | |
| BUREAU OF LAND MANA | AGEMENT RECEIVE | | |
| Sundry Notices and Rep | ports on Wells | | |
| | 201 APR 27 PM | 3: 37 - | Lease Number |
| | | э. | SF-081155 |
| 1. Type of Well GAS | 070 FARMINGTO | N, IGA | If Indian, All. or Tribe Name |
| • | | 7. | Unit Agreement Name |
| 2. Name of Operator | | , • | |
| BURLINGTON | | | |
| RESOURCES OIL & GAS COMPA | NY | | |
| | | 8. | Well Name & Number |
| 3. Address & Phone No. of Operator | | | Allison Unit #121S |
| PO Box 4289, Farmington, NM 87499 (50 | 5) 326-9700 | 9. | API Well No. 30-045-32136 |
| 4. Location of Well, Footage, Sec., T, R, | м | 10. | |
| 1765'FNL, 960'FWL, Sec.30, T32N, R6W, N | | | Basin Fruitland Coal |
| 1. | | 11. | County and State |
| \mathcal{A} | | 11. | San Juan Co, NM |
| 7/0 | | | |
| 12. CHECK APPROPRIATE BOX TO INDICATE NATU | The state of the s | OTHER | DATA |
| Type of Submission | Type of Action | e n | 1 |
| | lonment _X Chango Detion New Con | struct: | ion |
| | ng Back Non-Rout | ine Fra | acturing |
| | Repair Water S | | |
| Final Abandonment Alteri Other | ng Casing Convers | sion to | Injection |
| | | | |
| 13. Describe Proposed or Completed Opera The BOP configuration has been revised for attached diagram: BOP and tests: | | cording | to the following and |
| Surface to intermediate TD - 11" 2000 psi (minimum) do surface casing, test BOPE to 600 psi for 30 min. | ouble gate BOP stack (Refere | ence Figu | re #1). Prior to drilling out |
| Intermediate TD to Total Depth - 7 1/6" 2000 psi (minimuout intermediate casing, test BOPE and casing to 1500 p | | Referenc | e Figure #2). Prior to drilling |
| From surface to 7" TD – a choke manifold will be installed. When the cavitation completion rig drills the production #4). | | | |
| Pipe rams will be actuated at least once each day and b upper kelly cock valve with handle and drill string safety rig floor. 14. I hereby certify that the foregoing is true and con | valves to fit each drill string | | |
| \sim \sim \sim \sim \sim | | | and the second of second of the |
| Signed Kney Oltmans Tit | tle <u>Regulatory Special</u> | <u>list</u> Da | te 04/013/04 |
| (This space for Federal or State Office us | | | 184-20-00 |
| APPROVED BY / (Title CONDITION OF APPROVAL, if any: | leI | Date _ | AST WASON S |
| Title 18 U.S.C. Section 1001, makes it a crime for any person knowing United States any false, fictitious or fraudulent statements or repre | ly and willfully to make to any dep sentations as to any matter within | artment or its jurisdi | agency of the ction. |

BURLINGTON

PESCURCES

Figure #4

Cavitation Rig

BOP Configuration

2,000 psi Minimum System

